

Product data sheet

Characteristics

140CPS52400

power supply module - 125 V DC 100..150 V -
redundant - 8 A



Main

Range of product	A automation platform
Product component type	Power supply module
Power supply type	Redundant

Complementary

Input voltage	125 V DC 100...150 V
Input current	500 mA 125 V
Inrush current	28 A 125 V
Input power interruption	<= 1 ms
Associated fuse rating	2 A slow-blow
Output voltage	5.1 V DC
Power supply output current	8 A redundant
Output overvoltage protection	Internal
Output overload protection	Internal
Power dissipation	6 + (1.5 x I _{out}) where I _{out} is in A
Local signalling	1 LED green power (PWR OK)
Marking	CE
Module format	Standard
Product weight	0.65 kg


Environment

Standards	CSA C22.2 No 142 UL 508
Product certifications	CUL FM Class 1 Division 2
Resistance to electrostatic discharge	4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...2000 MHz conforming to IEC 801-3

Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots

125 Vdc/8 A Standalone/Redundant Power Supply Module

Wiring Diagram

