


DATA SHEET

Vibro-Meter®

## VM600 IOC4T input/output card



### KEY FEATURES AND BENEFITS

- From the Vibro-Meter® product line
- Signal interface card with 4 dynamic signal inputs and 2 tachometer (speed) inputs, for the MPC4 machinery protection card
- Screw-terminal connectors (48 terminals) for all input/output connections
- Contains 4 relays which can be attributed to alarm signals, under software control
- 32 fully-programmable open-collector outputs (jumper selectable) to IRC4 and RLC16 relay cards
- Buffered “raw” sensor signals and analog output signals (voltage or current) for vibration channels
- EMI protection for all inputs and outputs
- Live insertion and removal of cards (hot-swappable)
- Available in “standard” and “separate circuits” versions

### APPLICATIONS

- Machinery protection and/or basic condition monitoring



Information contained in this document may be subject to export control regulations of the European Union, USA or other countries. Each recipient of this document is responsible for ensuring that transfer or use of any information contained in this document complies with all relevant export control regulations. ECN N/A.

## DESCRIPTION

---

### IOC4T card

The IOC4T input /output card acts as a signal interface for the VM600 series MPC4 machinery protection card, from Meggitt's Vibro-Meter® product line. It is installed in the rear of a VM600 rack and connects directly to the rack backplane via two connectors.

Each IOC4T card is associated with a corresponding MPC4 card and is mounted directly behind it in the VM600 rack (ABE04x or ABE056). The IOC4T operates in slave mode and communicates with the MPC4, through connector P2, using an Industry Pack (IP) interface.

The front panel of the IOC4T (rear of the VM600 rack) contains terminal strip connectors for wiring to the transmission cables coming from measurement chains (sensors and /or signal conditioners). The screw-terminal connectors are also used to input all signals from and output all signals to any external control system.

The IOC4T card protects all inputs and outputs against electromagnetic interference (EMI) and signal surges and also meets electromagnetic compatibility (EMC) standards.

The IOC4T connects the raw dynamic (vibration) and speed signals from the sensors to the MPC4. These signals, once processed, are passed back to the IOC4T and made available on the terminal strip on its front panel (rear of VM600). For the dynamic signals, four on-board digital-to-analog converters (DACs) provide calibrated signal outputs in the range 0 to 10 V. In addition, four on-

board voltage-to-current converters allow the signals to be provided as current outputs in the range 4 to 20 mA (jumper selectable).

The IOC4T contains four local relays that can be attributed to any specific alarm signals under software control. For example, these may be used to signal an MPC4 fault or a problem detected by a common alarm (Sensor OK, Alarm and Danger) in a typical application.

In addition, 32 digital signals representing alarms are passed to the rack backplane and may be used by optional RLC16 relay cards and / or IRC4 intelligent relay cards mounted in the rack (jumper selectable).

### Applications information

When used as a card pair with an MPC4 machinery protection card, the IOC4T is highly suitable for machinery monitoring and protection in a wide range of industrial applications.

For further information on the use of MPC4/IOC4T card pairs in general, refer to the *VM600 machinery protection system (MPS) hardware manual* and the *VM600 MPSx software manuals*. For information on the use of MPC4/IOC4T card pairs in functional safety contexts, refer to the *VM600 functional safety manual*.

For specific applications, contact your local Meggitt representative.

## SPECIFICATIONS

---

### Dynamic signal inputs

Filtering

: Filtered for protection against electromagnetic interference (conforms to EC standards).  
Refer to the VM600 MPC4 machinery protection card data sheet for further information.

### Buffered dynamic signal outputs

Filtering

: Filtered for protection against electromagnetic interference (conforms to EC standards).  
Refer to the VM600 MPC4 machinery protection card data sheet for further information.

### Speed/phase reference inputs

Filtering

: Filtered for protection against electromagnetic interference (conforms to EC standards).  
Refer to the VM600 MPC4 machinery protection card data sheet for further information.

### Discrete signal interface (DSI) inputs

Control signal

- Alarm reset (AR)

: A closed contact between the DSI AR and DSI RET inputs resets (clears) the alarms latched by the MPC4/IOC4T card pair.  
Note: The alarm reset input (DSI AR) is edge-sensitive and a high-to-low transition is required to activate the reset.
  - Danger bypass (DB)

: A closed contact between the DSI DB and DSI RET inputs inhibits (bypasses) the danger relay outputs
  - Trip multiply (TM)

: A closed contact between the DSI TM and DSI RET inputs multiplies the alarm levels by a scale factor (software configurable), to enable adaptive monitoring.
- Operating principle
- : Detection of an open circuit or a closed circuit on the input

### Alarm outputs

Alarm relays

: 4 per IOC4T card.  
The MPC4 card can drive the four local relays on the IOC4T card, as well the relays on RLC16 relay cards and/or IRC4 intelligent relay cards using the VM600 rack's Raw bus or Open Collector (OC) bus. For IOC4T card relay features, see **Relay characteristics on page 4**. For further information on RLC16 or IRC4 relay cards, refer to the corresponding data sheet.

Note: In a VM600 rack (ABE4x), the Open Collector (OC) bus and/or Raw bus can be used to connect up to 32 outputs from an MPC4/IOC4T card pair to RLC16 relay cards or IRC4 intelligent relay cards in the same rack, if additional relays are required.

---


**SPECIFICATIONS** *(continued)*

**Analog (DC) outputs**

|                           |                                                                                                                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of outputs         | : 4 per IOC4T card (one per MPC4 dynamic signal channel)                                                                                                                                                                                                                  |
| Signal range              | : Current output (4 to 20 mA) or voltage output (0 to 10 V), individually selectable by a jumper on the IOC4T for each output.<br>Note: For current outputs, the analog output is actually driven in a slightly wider 2 to 23 mA range, proportional to the input signal. |
| Accuracy                  | : $\leq \pm 1.5\%$                                                                                                                                                                                                                                                        |
| Linearity error           | : $\leq \pm 0.5\%$                                                                                                                                                                                                                                                        |
| Admissible load on output | : $> 100\text{ k}\Omega$ for voltage output.<br>$< 325\text{ }\Omega$ for current output.                                                                                                                                                                                 |

**Relay characteristics**

|                                                           |                                                                                                         |
|-----------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Relay names                                               | : RL1 to RL4                                                                                            |
| Type                                                      | : PE014005                                                                                              |
| Contact arrangement                                       | : 1 x NC or 1 x NO contact per relay (user configurable).<br>The selected contacts are available on J2. |
| Nominal rated voltage                                     | : $250\text{ V}_{AC}$                                                                                   |
| Nominal rated current                                     | : $5\text{ A}_{AC}$                                                                                     |
| Maximum breaking capacity<br>(without contact protection) | : $1250\text{ VA}$                                                                                      |
| Maximum DC load breaking capacity curve:                  |                                                                                                         |



|                                   |                               |
|-----------------------------------|-------------------------------|
| Operate / release / bounce time   | : Typically 8 / 8 / 6 ms      |
| Dielectric strength test voltages |                               |
| • Between open contacts           | : $1000\text{ V}_{AC}$        |
| • Between contact and coil        | : $4000\text{ V}_{AC}$        |
| Mechanical life                   | : $15 \times 10^6$ operations |
| Electrical life                   | : $> 10^5$ operations         |

**⚠ When used in a VM600 slimline rack (ABE056) with a DC power supply, the relay contacts on an IOC4T card have a maximum switching voltage of  $70\text{ V}_{DC}$  /  $33\text{ V}_{AC (RMS)}$  ( $46.7\text{ V}_{AC (PEAK)}$ ).**

## SPECIFICATIONS *(continued)*

---

### Environmental

#### Temperature

- Operating : -25 to 65°C (-13 to 149°F)
- Storage : -40 to 85°C (-40 to 185°F)

#### Humidity

- Operating : 0 to 90% non-condensing
- Storage : 0 to 95% non-condensing

### Approvals

- Conformity : CE marking, European Union (EU) declaration of conformity.  
EAC marking, Eurasian Customs Union (EACU) certificate /  
declaration of conformity.
- Electromagnetic compatibility : EN 50081-2 and EN 50082-2.  
IEC/EN 61000-6-2 and IEC/EN 61000-6-4.  
TR CU 020/2011.
- Electrical safety : IEC/EN 61010-1.  
TR CU 004/2011.
- Vibration : IEC 60255-21-1 (Class 2)
- Insulation coordination for measuring  
relays and protection equipment : Separate circuits according to IEC 60255-5  
for the "separate circuits" version of the IOC4T
- Safety integrity level : SIL 1 according to IEC 61508
- Environmental management : RoHS compliant
- Russian federal agency for technical  
regulation and metrology (Rosstandart) : Pattern approval certificate CH.C.28.004.A N° 60224

### Communications

- MPC4 to IOC4T bus : Similar to industry pack (IP)

### Configuration

- MPC4/IOC4T card pair : Software configurable via an RS-232 or Ethernet connection, using  
a computer running the VM600 MPSx software.  
Hardware configurable using jumpers on the MPC4/IOC4T card  
pair.

Note: Configuration via an Ethernet connection requires a CPUx card acting as a rack controller in the VM600 rack.

### Status indicators (LEDs)

- SLOT ERROR : Used to indicate indicates whether the IOC4T is installed in the  
correct slot of the VM600 rack

### Power supply to card (input)

- Power source : VM600 rack power supply
  - Supply voltages : +5 V<sub>DC</sub> and ±12 V<sub>DC</sub>
  - Consumption from +5 V<sub>DC</sub> supply : 1.5 W
  - Consumption from ±12 V<sub>DC</sub> supply : 0.7 W, plus an additional 0.25 W per current output used
-

SPECIFICATIONS *(continued)*

Connectors

|    |                                                                                                                                                                                                                                                                      |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| J1 | : 16-contact screw-terminal connector.<br>Inputs (analog signals) for dynamic measurement channels 1 to 4.                                                                                                                                                           |
| J2 | : 16-contact screw-terminal connector.<br>Inputs (analog signals) for tachometer (speed) channels 1 to 2.<br>Outputs (contacts) for relays RL1 to RL4.                                                                                                               |
| J3 | : 16-contact screw-terminal connector.<br>Outputs (analog signals) for DC outputs 1 to 4.<br>Inputs (digital signals) for DSI control signals: AR, DB and TM.<br>Outputs (analog signals) for buffered "raw" sensor outputs for dynamic measurement channels 1 to 4. |

Physical

|        |                             |
|--------|-----------------------------|
| Height | : 6U (262 mm, 10.3 in)      |
| Width  | : 20 mm (0.8 in)            |
| Depth  | : 125 mm (4.9 in)           |
| Weight | : 0.25 kg (0.55 lb) approx. |

ORDERING INFORMATION

To order please specify

| Type  | Designation                                                 | Ordering number (PNR) |
|-------|-------------------------------------------------------------|-----------------------|
| IOC4T | Different versions of the input/output card (for the MPC4): |                       |
|       | – Standard                                                  | 200-560-000-1Hh       |
|       | – Separate circuits                                         | 200-560-000-2Hh       |

Notes

Versions of the IOC4T card are available with a conformal coating ("varnish") applied to the circuitry of the card for additional environmental protection against chemicals, dust, moisture and temperature extremes.

In 2017, the MPC4 / IOC4T machinery protection card pairs were improved to (1) be RoHS compliant and (2) provide a reduced buffered dynamic signal output impedance, which required a redesign of the underlying buffered "raw" dynamic signal output circuitry. Accordingly, the different versions of the MPC4/IOC4T machinery protection card pairs in use are:

- Later versions of the MPC4 (PNRs 200-510-SSS-115, 200-510-SSS-214 and 200-510-SSS-313 or later) and IOC4T (PNR 200-560-000-114 and 200-560-000-212 or later), which are RoHS compliant and have an output impedance of 50  $\Omega$ .
- Earlier versions of the IOC4T (PNRs 200-510-SSS-114, 200-510-SSS-213 and 200-510-SSS-312 or earlier) and IOC4T (PNR 200-560-000-113 and 200-560-000-211 or earlier), which are not RoHS compliant and have an output impedance of 2000  $\Omega$ .

"SSS" represents the firmware (embedded software) version and "Hh" the hardware version. "H" increments are for major modifications that can affect product interchangeability. "h" increments are for minor modifications that have no effect on interchangeability.

## RELATED PRODUCTS

|                   |                                                                                                                                                               |                                      |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| ABE04x            | VM600 system racks                                                                                                                                            | : Refer to corresponding data sheet  |
| ABE056            | VM600 slimline rack                                                                                                                                           | : Refer to corresponding data sheet  |
| AMC8 and IOC8T    | VM600 analog monitoring card pair                                                                                                                             | : Refer to corresponding data sheet  |
| CPUM and IOCN     | VM600 modular CPU card and input/output card.<br>Note: With a front-panel display and support for Modbus RTU/TCP or PROFINET.                                 | : Refer to corresponding data sheet  |
| CPUR and IOCR     | VM600 rack controller and communications interface card pair.<br>Note: With rack controller redundancy and support for Modbus RTU/TCP.                        | : Refer to corresponding data sheet  |
| CPUR2 and IOCR2   | VM600 rack controller and communications interface card pair.<br>Note: With mathematical processing of fieldbus data and support for Modbus TCP and PROFIBUS. | : Refer to corresponding data sheet  |
| IRC4              | VM600 intelligent relay card                                                                                                                                  | : Refer to corresponding data sheet  |
| MPC4              | VM600 machinery protection card                                                                                                                               | : Refer to corresponding data sheets |
| MPC4G2 and IOC4G2 | VM600 machinery protection card pair                                                                                                                          | : Refer to corresponding data sheet  |
| RLC16             | VM600 relay card                                                                                                                                              | : Refer to corresponding data sheet  |
| RLC16G2           | VM600 relay card                                                                                                                                              | : Refer to corresponding data sheet  |
| XMx16 and XIO16T  | VM600 condition monitoring card pairs                                                                                                                         | : Refer to corresponding data sheet  |

Meggitt (Meggitt PLC) is a leading international engineering company, headquartered in England, that designs and delivers high-performance components and subsystems for aerospace, defence and selected energy markets. Meggitt comprises four customer-aligned divisions: Airframe Systems, Engine Systems, Energy & Equipment and Services & Support.

The Energy & Equipment division includes the Energy Sensing and Controls product group that specialises in sensing and monitoring solutions for a broad range of energy infrastructure, and control valves for industrial gas turbines, primarily for the Power Generation, Oil & Gas and Services markets. Energy & Equipment is headquartered in Switzerland (Meggitt SA) and incorporates the Vibro-Meter® product line, which has over 65 years of sensor and systems expertise and is trusted by original equipment manufacturers (OEMs) globally.



All information in this document, such as descriptions, specifications, drawings, recommendations and other statements, is believed to be reliable and is stated in good faith as being approximately correct, but is not binding on Meggitt (Meggitt SA) unless expressly agreed in writing. Before acquiring and/or using this product, you must evaluate it and determine if it is suitable for your intended application. You should also check our website at [www.meggittsensing.com/energy](http://www.meggittsensing.com/energy) for any updates to data sheets, certificates, product drawings, user manuals, service bulletins and/or other instructions affecting the product.

Unless otherwise expressly agreed in writing with Meggitt SA, you assume all risks and liability associated with use of the product. Any recommendations and advice given without charge, whilst given in good faith, are not binding on Meggitt SA. Meggitt (Meggitt SA) takes no responsibility for any statements related to the product which are not contained in a current Meggitt SA publication, nor for any statements contained in extracts, summaries, translations or any other documents not authored and produced by Meggitt SA.

The certifications and warranties applicable to the products supplied by Meggitt SA are valid only for new products purchased directly from Meggitt SA or from an authorised distributor of Meggitt SA.

In this publication, a dot (.) is used as the decimal separator and thousands are separated by thin spaces. Example: 12345.67890.

Copyright© 2019 Meggitt SA. All rights reserved. The information contained in this document is subject to change without prior notice.