Guangdong EverRay Enviromental Material Co., Ltd.
Office Add.：12th Floor,Tower B, AOYUAN Plaza, Pengjiang District, Jiangmen
Tel：0750-3380698、3380676
Fax：0750-3380681、3380636
http://www.ever-ray.com

PRODUCT MODEL： 71209A-1

Polyurethane Acrylate 71209A-1

TECHNICAL FEATURES：	Appearance	Transparent viscous liquid
	Viscosity（mPa.s）	15000～35000(25℃)
	Functionality	2
	Chrominance（Pt-Co)	≤80
	NCO%	〇

COMPATIBILITY： This product is compatible with most UV monomers and UV curable resins.

APPLICATION： This product features fast reactivity, excellent alcohol solubility, high toughness, and strong resistance to fracture. It is recommended for use in fields such as LED 3D printing and ink varnishes

PACKAGING： 20/200 (kg)/Closed ordinary steel bucket

STORAGE： This product should be stored and transported in dark opaque steel drums or containers containing corrosion-resistant and solvent resistant coatings. Leave at least 15% space inside the container filled with air. Packaging should be stored in a cool environment below 35 ℃, and exposure to sunlight is strictly prohibited.

GUARANTEE PERIOD： 180 days.

This material is for reference only and is not intended as a basis for actual use by customers, and customers should confirm their applicability before use, and any amendments will be made without notice.