

2.7-3.1GHz/2000Watt/Module

Model Number: KNP2900M63A

KNP2900M63A is an S-band high power pulsed amplifier operating in the 2.7GHz-3.1GHz frequency range and offering pulse width up to 10μs with duty cycle up to 10%. The amplifier provides 2000 Watts peak output power into a 50 Ohm load. The employment of gallium nitride (GaN) in manufacturing ensures this module state-of-the-art power performance with excellent power-to-volume ratio. It is ideal for high power pulse applications or radar system.

FEATURES:

- Small size and light weight
- Power added efficiency > 15%
- Pulse width&duty cycle protection
- Over voltage&over current protection

ELECTRICAL SPECIFICATIONS @ +50.0VDC, 25°C, 10μS, 10%, 50Ω

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	2.7		3.1	GHz
RF Output Power	PPK		2000		Watt
Duty Cycle	Duty Cycle			10	%
Pulse Width	PWIDTH	0.5		10	μS
PRI	PRI	50		1000	μS
Harmonics @ Pout = 1000W	H		-30		dBc
Spurious Signals	Spur		-55		dBc
RF Input Power @ Pout = 2000W	PIN		0		dBm
Input Return Loss	S11		-10		dB
Rise /Fall time (Pulse Performance)(10-90%)	TRISE/FALL		100		nS
Switching Speed	TON/OFF		2		μS
Power droop	Droop		1		dB
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC	48	50	52	Volt
Peak Current Consumption @ Pout =2000W	IDD			120	Amp
Average Current Consumption @ Pout = 2000W	IDD		24		Amp

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	300x280x25 [11.81x11.02x0.98]	mm [inch]	Max
Weight	6 [13.2]	kg [lb]	Max
RF Connector Input	SMA, Female		
RF Connector Output	Type-N, Female		
DC Interface Connector	Hybrid, D-Sub 7-Pin, Male		
Cooling	External Heatsink Required (Optional supplying)		

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-40		60	°C	
Non-operating Temperature	-45		85	°C	Storage
Relative Humidity (non-condensing)			95	%	

Focus on Your Application***Chengdu KeyLink Wireless Technology Co., Ltd.***

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice

2.7-3.1GHz/2000Watt/Module

Model Number: KNP2900M63A

ABSOLUTE MAXIMUM RATING


Input RF drive level without damage	+5 dBm (Max)
Load VSWR @ POUT =500W	∞ @ all load phase & amplitude for duration of 1minute; 3:1 @ all load phase & amplitude continuous
Over Temperature	85°C @ heatsink [restored @ 60°C]

DC INTERFACE CONNECTOR

Pin #	Description	Specifications
A1	GND	Ground
A2	VDD	50VDC
1	ALARM	Amplifier Alarm indicator: Normally TTL Low
2	CURRENT SENSE	Analog voltage relative to IDD @ 100mV±10% per Ampere
3	TEMP SENSE	Analog voltage relative to Module's Temperature @ 0.5V+10 mV/°C
4	RF ON/OFF	RF On: TTL Logic High (3.3V)
5	Enable	Amplifier Enable: TTL Logic High (Internally Pulled-Low)

*The temperature sense accuracy is ±10℃

OUTLINE DRAWING (All dimensions in mm [inch])



Focus on Your Application

Chengdu KeyLink Wireless Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266


>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice

2.7-3.1GHz/2000Watt/Module

Model Number: KNP2900M63A

TYPICAL PERFORMANCE PLOTS (For Reference Only)



Note:

1. Adequate heatsink required.
2. This product will be developed upon contract/order. All the above specs are for reference only. Actual product may be different. Please check with KeyLink sales team if you have any questions.

Focus on Your Application

Chengdu KeyLink Wireless Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266

>> Email: sales@keylinkmw.com >> www.keylinkmw.com

Specifications subject to change without notice