

Attestation of Conformity

No. N8A 121865 0002 Rev. 00

Holder of Attestation: Jiangxi Huntec Electrical Technology

Co., Ltd

No.1829 Yangguang Avenue, High-tech Development Zone

338000 Xinyu City, Jiangxi Province PEOPLE'S REPUBLIC OF CHINA

Product: Terminal block

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105233111601

Date, 2023-08-16

(Martin Ma)

Warfin Mer

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Attestation of Conformity

No. N8A 121865 0002 Rev. 00

Model(s): RES-P-10/25-B-30-BK, RES-P-10/25-B-30-OG,

RES-P-10/25-B-30(S)-BK, RES-P-10/25-B-30(S)-OG,

RES-P-35/70-B-30-BK, RES-P-35/70-B-30-OG,

RES-P-35/70-B-30(S)-BK, RES-P-35/70-B-30(S)-OG

Parameters:

| Rated impulse withstand voltage (U _{imp}): | 8kV | | | |
|--|--|--|--|--|
| Ability to receive conductors: | Rigid / stranded / flexible (prepared conductor, with lug) | | | |
| Type of clamping units: | Screw-type | | | |
| Number of clamping units: | 1 | | | |
| Number of poles: | 1 | | | |
| Method of fixing: | Fix with screw | | | |

| Model | Rated insulation voltage U _i (VDC) | Conventional free air thermal current I _{th} (A) | Rated connection capacity (mm²) | Rated cross- section (mm²) |
|------------------------|--|---|---------------------------------------|-------------------------------------|
| RES-P-10/25-B-30-BK | 1500 | 120 | 10 - 25 | 25 |
| RES-P-10/25-B-30-OG | 1500 | 120 | 10 - 25 | 25 |
| RES-P-10/25-B-30(S)-BK | 1500 | 120 | 10 - 25 | 25 |
| RES-P-10/25-B-30(S)-OG | 1500 | 120 | 10 - 25 | 25 |
| RES-P-35/70-B-30-BK | 1500 | 250 | 35 - 70 | 70 |
| RES-P-35/70-B-30-OG | 1500 | 250 | 35 - 70 | 70 |
| RES-P-35/70-B-30(S)-BK | 1500 | 250 | 35 - 70 | 70 |
| RES-P-35/70-B-30(S)-OG | 1500 | 250 | 35 - 70 | 70 |

Tested EN 60947-7-1:2009 EN 60947-1:2007/A2:2014 EN IEC 60947-1:2021

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

