








1		2		3		4		5		6		7		8							
未注公差/General tolerances(mm)														符号/SIGN		描述/DESCRIPTION		修订者/DRAWN		日期/DATE	
>0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10	±2c						
~	~	~	~	~	~	~	~	~	~	~	~	~	~								
±0.15	±0.20	±0.25	±0.30	±0.35	±0.40	±0.60	±0.80	±0.95	±1.00	±1.20	±1.60	±2.20	±2.50								



技术参数 Technical parameter:

● 产品标准/Rated Voltage	UL486C	GB13140	IEC60998	
● 获得安规及标志 Access to Safety Mark				
● 证书号码/Certificate No	E348667	CQC1900 3235085	40049102	
● 额定电压/Rated Voltage	600V	400V	400V	
● 额定电流/Rated Current		24A	32A	
● 线径范围/Wire range		0.2~2.5mm ²	0.2~4.0mm ²	
● 硬质导线/Solid wire(AWG)	28~16AWG			
● 软质导线/Stranded wire(AWG)	28~16AWG			
● 剥线长度/Wire strip length	9~10mm	10mm	9~10mm	
● 绝缘耐压/Withstanding Voltage	2200V	2500V	2500V	
● 温度范围/Operating temperature	-40℃~105℃			
● 焊接温度/Soldering temperature	/			
● 关键尺寸/Critical dimension	★			

FUCON	CAT NO./认证型号	CM-222	SHEET: 1/1
	PATE NO./成品料号	01.04.005.0002	SCALE: 1:1
	CUST NO./客户料号	/	REV.: A01
APPROVED/审批	何跃雄 2021.12.15	MODEL:	CM-222-3P
CHECKED/核准	胡德权 2021.12.15	DRAWING NO./图号:	
DRAWN/制图	陈燕龙 2021.12.15	TYPE/图纸类型:	CUSTOMER_DRAWING
SIZE: A4			

④	端子/Terminal	紫铜+不锈钢		3
③	手柄/Handle	PA6 UL94V-2	橙色	3
②	上盖/Cover	PA6 UL94V-0	灰色	1
①	主座/Housing	PA6 UL94V-0	灰色	1
ITEM 序号	NAME OF PART 部件名称	Material 材料	NOTES 备注	QTY 用量