










## Panel Mounting Type USB Connector

- Shell material: Engineering plastic (silver white and black optional)
- Fixed by nut, easy to install.
- Operating Temperature: -25°C~+55°C(NO Freezing)
- Pane Cutout:  $\Phi 22\text{mm}$
- Panel Thickness: 1~10mm
- Transmission Rate:  $\geq 30\text{MB/s}$
- Operating Humidity: 45~85%RH(NO Condensation)













USBBC-10  
Double-layer USB3.1 Head Female C / Back Male C  
Wire Length: About 100cm



USBBC-11  
USB3.1 Head Female C / Back Male C  
Wire Length: About 100cm



Mini USB-01  
Mini USB2.0 Head Female B / Back Male B



USBBC-10-BK  
Double-layer USB3.1 Head Female C / Back Male C  
Wire Length: About 100cm



USBBC-11-BK  
USB3.1 Head Female C / Back Male C  
Wire Length: About 100cm



Mini USB-01-BK  
Mini USB2.0 Head Female B / Back Male B



Mini USB-04  
Mini USB2.0 2xFemale B / Male B



Micro USB-01  
Micro USB2.0 Female B / Male B



Micro USB-02  
Micro USB2.0 2xFemale B / Male B  
Wire Length: About 60cm



Mini USB-04-BK  
Mini USB2.0 2xFemale B / Male B



Micro USB-01-BK  
Micro USB2.0 Female B / Male B



Micro USB-02-BK  
Micro USB2.0 2xFemale B / Male B  
Wire Length: About 60cm



Micro USB-03  
Micro USB2.0 2xFemale B / Male B



Micro USB-04  
Micro USB2.0 Female B / Male B  
Wire Length: About 60cm



Micro USB-03-BK  
Micro USB2.0 2xFemale B / Male B



Micro USB-04-BK  
Micro USB2.0 Female B / Male B  
Wire Length: About 60cm



