

PRODUCT DATA SHEET

CP-55 Micro Glass Bead for Oil Well Cement**Product Description**

CP-55 is the high performance cenosphere. It is mainly used lightening agent in low density cement slurry.

Characteristics

- CP-55 is the high performance micro glass bead, it has lower density, small thermal conductivity, high compression strength, good fluidity and chemical stability, etc.
- Appearance: White powder.
- Normal dosage: 1.0% ~ 10%(BWOC). It can be used in compounding cement slurry with density between 1.25~1.80 willfully. Reducer its dosage with the increase of the cement slurry, and decrease the ratio of water to cement. Its thickening time, theology and content of free water can meet the demands of construction.
- Preferred by dry mixing.

Technical Specification

- | | |
|-----------------------------------|--------------------------|
| • Appearance | white powder |
| • Water content, % | ≤ 2% |
| • True density, g/cm ³ | 0.6~0.9g/cm ³ |

Packing, Storage

- Packed in tri-layer paper bags with polyethylene liner, 10kg/bag or packed according to the request of clients.
- Placed in dry, ventilated, shady and cool circumstance.
- Be kept away from harmful substance in store and transportation.
- Its life span is TWO years.

For more information on CP-55, please call your
local Oilchemleader representative or email us at info@ocl.com.cn