

LXD-618 Driving type thermoplastic screeding (convex) type road marking machine



Technical Data

Engine	25HP Honda GX690 Gasoline Engine(Gasoline, capacity 0.054m ³) OR Kubota V1505 type diesel engine(net power:26.1KW)
Electronic system	LXD electronic control system
Steering	Powerful standard mechanical steering system according to the requirements mentioned
Drive / braking system	Hydrostatic transmission, also used as service brake, parking brake hydraulically controlled multi-disc brake
Wheel	6.00-9NHS * 4
Compressor	0.21m ³ / min
Working pressure	7bar, Silent safety valve
Power Systems	12V
Thermoplastic container	0.39m ³ , with hydraulic agitator (According to customer requirements)
Heating method	Gas heating
Additional equipment	Available with 15.20.30.40cm scraper, oscillating bucket (customized as required)

Additional equipment	on request, profiles
Discharge	Pneumatic Opening/closure,with pedal controls
Glass beads Equipment	Spraying, adjustable pressure
Glass beads Tank Capacity:	0.07m ³
Machine Weight	About 1600kg
Machine Size	About length 4m (not include pointer) * width 1.4 (not include shoe) m* height 2.2 m (adjustable)



Sales Manager: James Zhang

Company name: Jiangsu Luxinda Traffic Facilities Co.,Ltd.

Tel:+86-511-87059003

Mob:+86 15862991398

Wechat/Whatsapp:+86 15862991398

Email: sales@trafficmarkingmachine.com

Website: www.trafficmarkingmachine.com