

LXD-618 Driving type cold plastic spray road marking machine(double pump)



Engine	Kubota Diesel engine, net power:26.1KW
Fuel	Diesel oil
Electronic system	LXD electronic system, Electronic system with display for control and showing of machine operation functions
Coating technology	airless, under high pressure
steel	Powerful standard mechanical steering systems are available upon request
Drive/brake system	Hydrostatic transmission, also used as a driving brake, multi disc brake controlled by parking brake hydraulic
Movement	Self-propelled with 4 wheels
wheel	6.00-9NHS* 4 wheels
compressor	0.52m³/min
Working pressure	7bar, Mute relief valve

electrical power system	12V
hydraulic pump	Double Graco Pump
Max flow	16L/min*2 Pump
Paint pump control mode	Automatic reciprocating cylinder
line thickness	0.2-0.4mm（adjustable）
Line width	100-900mm（adjustable）
Spray gun quantity	2 pneumatic spray guns and 1 manual spray gun（addtional on request）
Paint tank capacity	0.23m³*2(can be customized according to reuqirement)
Glass beads system	dispenser and automatic gun, working pressure adjustable
Glass beads tank capacity	0.07m³,
Size	Approximately 4m（length）* 1.4（width） m* 2.2 m（height）

Sales Manager: James Zhang

Company name: Jiangsu Luxinda Traffic Facilities Co.,Ltd.

Mob:+86 15862991398

Wechat/Whatsapp:+86 15862991398

Email: sales@trafficmarkingmachine.com

Website: www.trafficmarkingmachine.com