

LXD1500 High efficiency energy saving type thermoplastic preheater



technical parameter	
engine	10PS Air-cooled electrical starting diesel engine
Internal structure of the body	frame structure, There are thermal insulation material between the inner and outer cover plates
	Double helix full tank heating system
Hydraulic transmission system	Hydraulic two-way stepless mixing, Motor: BM315
hydraulic oil tank	0.063m ³
Diesel oil tank	0.095m ³
Heating system	Imported diesel stoves, automatic ignition,, intelligent temperature control system
Paint tank capacity	about 0.815m ³ , can accommodate about 1500KG

	thermoplastic paint
dimension	1850×1200×2150mm (single tank type)
weight	1150kg (single tank type)

Advantages:

- 1. Automatic ignition:**The key opens the stove without manual ignition
- 2. The bottom of the pot has a long service life:** The whole pot is heated by combustion chamber,The heating area of the pot is increased by 3.5 times,No longer heat the bottom of the pot on one side,The bottom of the pot will not be damaged, and the materials in the pot will not be scorched.
- 3. Intelligent temperature control system:** When the temperature is higher than the set value, the stove will automatically shut down, and when the temperature is lower than the set value, the stove will automatically ignite, which can reduce the unnecessary waste of diesel oil.
- 4. Fuel saving:** imported stove, diesel can be fully burned, there will be no black smoke in use, no waste of diesel.
- 5. Paint tank capacity:** 1.625 tons (single tank) at a time, large capacity.
- 6. It takes up less space:** 1.5T single tank type thermoplastic preheater is 25% smaller than the original 1.2t double cylinder thermoplastic preheater. 1.5T single tank type thermoplastic preheater no more liquefied gas heating,do not need to carry liquefied gas tank. The extra area can be used for stacking materials, greatly increasing the construction efficiency every day.
- 7. Single tank can replace double tank:** when the yellow paint is changed to white paint, it can be cleaned quickly manually. There are two feeding ports on the cauldron panel, which are equal to two cleaning ports. The long handle blade can be used to clean the yellow material without several packages of white material heating. When the white material is replaced with yellow material, there is no need to clean it.

Sales Manager: James Zhang

Company name: Jiangsu Luxinda Traffic Facilities Co.,Ltd.

Tel:+86-511-87059003

Mob:+86 15862991398

Wechat/Whatsapp: +86 15862991398

Email: sales@trafficmarkingmachine.com

Website: www.trafficmarkingmachine.com