

13.3-inch Industrial Tablet PC



KTB-PM133

13.3-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM133 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM133 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

13.3-inch Industrial Tablet PC

Product Features:

- 13.3-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall - mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built - in multi - functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM133	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM133	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	13.3" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	330mm*202mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

15-inch Industrial Tablet PC



KTB-PM150

15-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1024 x 768

The KTB-PM150 is an industrial tablet PC of KTB, supporting a resolution of 1024*768. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM150 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

15-inch Industrial Tablet PC

Product Features:

- 15-inch touch screen with a resolution of 1024*768
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM150	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM150	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	15" 4:3	
Resolution	1024*768	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	346mm*270mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

15.6-inch Industrial Tablet PC



KTB-PM156

15.6-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM156 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM156 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

15.6-inch Industrial Tablet PC

Product Features:

- 15.6-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V



*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM156	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM156	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	15.6" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	375mm*225mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

17-inch Industrial Tablet PC



KTB-PM170

17-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1024 x 768

The KTB-PM170 is an industrial tablet PC of KTB, supporting a resolution of 1024*768. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM170 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

17-inch Industrial Tablet PC

Product Features:

- 17-inch touch screen with a resolution of 1024*768
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM170	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM170	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	17" 5:4	
Resolution	1024*768	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	380mm*317mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

18.5-inch Industrial Tablet PC



KTB-PM185

18.5-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM185 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM185 supports wall-mounted, and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

18.5-inch Industrial Tablet PC

Product Features:

- 18.5-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM185	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM185	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	18.5" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	450mm*271mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

19-inch Industrial Tablet PC



KTB-PM190

19-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1280 x 1024

The KTB-PM190 is an industrial tablet PC of KTB, supporting a resolution of 1280*1024. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM190 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

19-inch Industrial Tablet PC

Product Features:

- 19-inch touch screen with a resolution of 1280*1024
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall - mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built - in multi - functional PCIe expansion slot for more function expansions.
- DC 12V



*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM190	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM190	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	19" 5:4	
Resolution	1280*1024	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	419mm*344mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

21.5-inch Industrial Tablet PC



KTB-PM215

21.5-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM215 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM215 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

21.5-inch Industrial Tablet PC

Product Features:

- 21.5-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V



*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM215	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM215	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	21.5" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	515.5mm*307mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

23.8-inch Industrial Tablet PC



KTB-PM238

23.8-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM238 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM238 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

23.8-inch Industrial Tablet PC

Product Features:

- 23.8-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM238	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM238	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	23.8" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	565mm*338mm*50.3mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

27-inch Industrial Tablet PC



KTB-PM270

27-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM270 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM270 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

27-inch Industrial Tablet PC

Product Features:

- 27-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall-mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built-in multi-functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM270	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V	

Model	KTB-PM270	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When 1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for WiFi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	27" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	652mm*390mm*56.5mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]

32-inch Industrial Tablet PC



KTB-PM320

32-inch Industrial Tablet PC
Capacitive touch screen
Resolution: 1920 x 1080

The KTB-PM320 is an industrial tablet PC of KTB, supporting a resolution of 1920*1080. The processor options include J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generations.

The KTB-PM320 supports wall-mounted and desktop installation methods. It adopts an aluminum-magnesium alloy panel with a surface protection rating of IP65. Equipped with multi-point capacitive touch technology and a flat design, the rear shell features a new concept of a fully enclosed shape. It is made of integrally die-cast aluminum alloy for heat dissipation, which endows it with stronger waterproof and dustproof capabilities and makes it more adaptable to harsh industrial environments.

32-inch Industrial Tablet PC

Product Features:

- 32-inch touch screen with a resolution of 1920*1080
- Processor options J1900/J4125/J4105/J6412/N100/3/4/7/8/10/11/12th generation
- Supports wall - mounted and desktop installations
- It provides multiple USB ports, COM ports, LAN ports, etc., to meet different needs of users.
- It has a built - in multi - functional PCIe expansion slot for more function expansions.
- DC 12V




*The reference image is KTB-PM215.

Ordering Information:

Model	Configuration
KTB-PM320	J1900/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4125/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J4105/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	J6412/2*LAN/2*USB (optional 1*LAN/4*USB)/VGA+HDMI/12V
	N100/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I3/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I5/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V
	I7/1*LAN/4*USB (optional 2*LAN/2*USB)/VGA+HDMI/12V

Model	KTB-PM320	
Processor	Intel® Celeron® J1900/J6412/J4125/J4105/N100 Intel® Core™ i3/i5/i7 3/4/7/8/10/11/12th generation are optional	
Memory	J1900/3/4th	J4125/J4105/J6412/N100/7/8/10/11/12th
Architecture	DDR3	DDR4
Capacity	Up to 8/16GB	Up to 8/16/32/64GB
I/O interface	1*HDMI;1*VGA; 2*LAN/1*LAN (When1*LAN optional 2*USB) 4*USB; 2*COM(Up to 6, Among them, COM2/4 optional RS485) 1*Line-out, 1*Mic-in	
Watchdog	255-level programmable settings	
GPIO	It supports the GPIO function with 4-channel input and output (optional)	
Expansion Slot	1*miniPCIe(Optional support for Wifi/4G module), 1*PCIe; 1*MSATA; 1*SATA; 1*M.2	
OS	Windows, Linux	
Power supply	12V/5A	
Screen size	32" 16:9	
Resolution	1920*1080	
Brightness	200-300cd/m ² (High-brightness customization is available)	
Cutout size	/	
Overall unit size	755mm*450mm*63mm	
Whole unit weight	/	
Touchscreen	Capacitive touch screen	
Structural material	Aluminum shell, fanless flat, IP65 front panel	
Border color	Silver black	
Installation type	Wall-mounted, desktop installation methods	
Working environment	0~50°C	
Storage environment	-20°C~60°C	
Certification	CCC CE ROHS	

Dimensions



Unit: mm[inch]