



XF-MH06X175

Specification

Magnification	0.6
Object field of view	$\Phi 18.3\text{mm}$
Image field of view	$\Phi 11\text{mm}$
Working Distance	$175\text{mm} \pm 3\%$
Depth of field	2.1mm
F#	F7.5
Resolution	$8.3\mu\text{m}$
MTF	$>0.3@125\text{lp/mm}$
Distortion	$<0.021\%$
Detector type:	
2/3'	8.45×7.07 $14.1 \times 11.8\text{mm}$
1/1.8'	7.2×5.3 $12 \times 8.8\text{mm}$
1/2'	6.4×4.8 $10.7 \times 8\text{mm}$
1/3'	4.8×3.6 $8 \times 6\text{mm}$

Undefined tolerance (mm)	degree	File Name		
X. X	± 0.2	$\pm 30\text{min}$	XF-MH06X175-外形尺寸-EN	
X. XX	± 0.02	Drawing Name		
X. XXX	± 0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:1
Modify1			Qty	
Modify2			Total:	Page:
			Canrill OPTICS <small>All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.</small>	