

Power Splitter

950X092X

- **Wide-band design, cover 500-6000MHz**
- **Low PIM < -160dBc**
- **Compact size and light weight**
- **Easy to be installed**
- **Suitable for indoor and outdoor applications**
- **Square tube**



Technical Data

Electrical Specifications

Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95020923	95030923	95040923
		≤-155	95020925	95030925	95040925
		≤-160	95020927	95030927	95040927
Frequency Range (MHz)		550-6000			
For connecting...antennas		2 Way	3 Way	4 Way	
Distribution Loss(dB)		3.0	4.8	6.0	
Insertion Loss (dB)		< 0.3	< 0.8	< 0.9	
Return Loss (dB)		≥19@550-2700&≥18@3400-6000			
Input Power (W)		≤300			
Peak Power (W)		≤800			
Impedance (Ω)		50			

Mechanical Specifications

Dimensions, HxWxD (excluding connectors and mounting bracket) (mm)	227.2x25x25	252.3x25x25	271.8x25x25
Weight (including connectors and mounting bracket) (kg)	0.40	0.46	0.52
Packing Size(mm)	290x85x50	335x85x50	355x85x65
Connector Type	N Female (Twist head)		
Color	Light Gray (Customized)		
Mounting	Wall Mounted		

Environmental Specifications

Operational Temperature (°C)	-25 to +65
Operational Humidity (%)	≤95
Ingress Protection Class	IP65(Indoor and Outdoor)

Accessories (order separately)

Type No.	Description
30505.0043051	Bracket
50501.0330100	Screw

Outline Drawing

