

Hybrid Combiner

95322XXX



- **Wide-band design, cover 340-3800MHz**
- **Low PIM**
- **Compact size and light weight**
- **Easy to be installed**
- **Suitable for indoor and outdoor applications**
- **Connector Type: Twist head**



Technical Data

Electrical Specifications

Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95322083	95322103	95322123
		≤-155	95322085	95322105	95322125
	≤-160	95322087	95322107	95322127	
Frequency Range (MHz)		340-3800			
Insertion Loss (dB)		3.1±1.2@340-698MHz 3.1±0.6@698-3800MHz			
Isolation (dB)		≥26			
VSWR (dB)		< 1.25			
Input Power (W)		<300	<300	<500	<500
Peak Power (W)		<800	<1500	<2000	<2000
Impedance (Ω)		50			

Mechanical Specifications

Dimensions, HxWxD (excluding connectors and mounting bracket) (mm)	226.9x48.6x42.5		
Weight (including connectors and mounting bracket) (kg)	1.0	1.3	1.5
Connector Type	N Female	4.3-10 Female	7-16 Female
Packing Size(mm)	280x150x95		
Color	Light Gray (Customized)		
Mounting	Wall Mounted		

Environmental Specifications

Operational Temperature (°C)	-35 to +65
Operational Humidity (%)	≤95
Ingress Protection Class	IP65 (Indoor and Outdoor)

Outline Drawing

