

Hybrid Combiner

95322XXX

HILINKS

- *Wide-band design, cover 550-4200MHz*
- *Low PIM*
- *Compact size and light weight*
- *Easy to be installed*
- *Suitable for indoor and outdoor applications*
- *Connector Type: Twist head*



Technical Data

Electrical Specifications					
Type No.	PIM3 (@2x43 dBm Carrier) (dBc)	≤-150	95322793	95322803	95322813
		≤-155	95322795	95322805	95322815
		≤-160	95322797	95322807	95322817
Frequency Range (MHz)		550-4200			
Insertion Loss (dB)		3.1±0.6			
Isolation (dB)		>25			
VSWR (dB)		< 1.25			
Input Power (W)		<300	<300	<500	
Peak Power (W)		<800	<1500	<2000	
Impedance (Ω)		50			
Mechanical Specifications					
Dimensions, HxWxD (excluding connectors and mounting bracket) (mm)		167.9X56.4X43			
Weight (including connectors and mounting bracket) (kg)		0.857	0.927	1.037	
Connector Type		N Female	4.3-10 Female	7-16 Female	
Packing Size(mm)		231X96X85			
Color		Light Gray (Customized)			
Mounting		Wall Mounted			
Environmental Specifications					
Operational Temperature (°C)		-40 to +65			
Operational Humidity (%)		≤95			
Ingress Protection Class		IP65 (Indoor and Outdoor)			

Outline Drawing

