BIT-PT510

Small Size Light Duty Pan Tilt Unit/Positioner
Top Load Capacity 10kg/20.05lb



Key Features:

- Maximum top load capacity 10kg/20.05lb
- Pan angle: 0-360°; Tilt angle: -60°~-+60°
- Pan speed 0.01~30°/s; Tilt speed 0.01~15°/s
- Preset accuracy: ±0.1°
- High precision stepper motor and tilt worm gear drive
- Support coordinate feedback and control
- 4000V lighting surge protection
- Upside down installation supported
- Rated IP66 for dust and water ingress


General Description:

BIT-PT510 is small size light duty pan tilt unit for both indoor/outdoor application. With a maximum 10kg/20.05lb load capacity, its pan rotation speed can be up to 30°/s.

Taking advantage of its high precision stepper motor and worm/gear drive mode, it features 0.1 degree positioning accuracy for repeat positioning and extremely low speed control. It also features 360 degree pan rotation and -60°~-+60°tilt rotation for wide angle surveillance.

Camera housings are also available for your easy integration with cameras.

Dimension:



Blue Icon (Tianjin) Technology Co., Ltd.
F9, Macalline Business Center
No. 29, Heiniucheng Rd.
Hexi District 300210
Tianjin, China

Email: sales@bit-cctv.com
Phone: +86-13920688922
Website: https://www.bit-cctv.com
Youtube: https://youtube.com/@bitcctvsolutions

Specifications:


Model	BIT-PT510
Max. Load Capacity	10kg/20.05lb top load (Upside down installation supported)
Rotation Angle	Pan: continuous 360°, Tilt: -60°~+60°
Rotation Speed	Pan: 0.01°/s-30°/s, Tilt: 0.01°/s-15°/s
Preset Accuracy	± 0.1°
Programmable Presets	255
Cruising Track	8, each with 10 preset positions
Scan	1
Position Feedback	Support position query/feedback via RS485 or optional real-time feedback via RS422
Absolute Position	Support
Guard Location	Support with a time period of 1-60 mins
Power Failure Memory	Support, back to PT position, scan/preset movement before power failure
Self-lock	Support
Start Movement	A series of movements for calibration when the unit is powered on
Protocol	Pelco P/D
Communication Interface	RS485,RS422 or RS232
Baud Rate	2400/4800/9600/19200 bps
Transmission	Worm gear
Standard Wiring/Interface	
Pan Tilt Base	100M Ethernet pass-through (4 wire), RS485 input (2 wire), 24VDC input (2 wire), GND
Pan Tilt Top	100M Ethernet pass-through (4 wire), RS485 input (2 wire), 12V DC output (2 wire), 24V DC output(2 wire), GND

Blue Icon (Tianjin) Technology Co., Ltd.
F9, Macalline Business Center
No. 29, Heiniucheng Rd.
Hexi District 300210
Tianjin, China

Email: sales@bit-cctv.com
Phone: +86-13920688922
Website: https://www.bit-cctv.com
Youtube: https://youtube.com/@bitcctvsolutions

General	
Operating Voltage	DC24V±10 %
Power Consumption	≤30W
Lighting Surge Protection	Power: 4000V (line to ground: 4000V, line to line: 2000V) ommunication signal interface: 2000V (line to ground:2000V, line to line: 1000V)
Working Temperature	-35ºC~+65 ºC
Working Humidity	90±5% RH
Storage Temperature	-40 ºC~+70 ºC
Protection Level	IP66
Material	Aluminium Alloy
Weight	5.5kg/12.13lb
Dimension L×W×H	223×140×235mm/8.78x5.51x19.25in (L*W*H)

Standard Wiring:



Blue Icon (Tianjin) Technology Co., Ltd.
F9, Macalline Business Center
No. 29, Heiniucheng Rd.
Hexi District 300210
Tianjin, China

Email: sales@bit-cctv.com
Phone: +86-13920688922
Website: https://www.bit-cctv.com
Youtube: https://youtube.com/@bitcctvsolutions

BIT-PT510

Small Size Light Duty Pan Tilt Unit/Positioner
Top Load Capacity 10kg/20.05lb

Image Gallery:



FRONT



BACK



SIDE



TRIPOD

Blue Icon (Tianjin) Technology Co., Ltd.
F9, Macalline Business Center
No. 29, Heiniucheng Rd.
Hexi District 300210
Tianjin, China

Email: sales@bit-cctv.com
Phone: +86-13920688922
Website: https://www.bit-cctv.com
Youtube: https://youtube.com/@bitcctvsolutions