ANDELI

H.R.C

H.R.C Fuse Core



RO14 RO15 RO16 RO21 RO22

1. Application

The fuses links having cylindrical contact caps are designed for protecting electrical distributing installations of rated voltage of 380V AC. with rated current up to 125A against damage due to overload and short circuit. Fuse links with the striker are supplied for the purpose of protecting motors against motor single phasing operation when fitted in fuse isolators.

2. Specifications

Type		Dimension	Rated Current
gG	aR	(mm)	(A)
RO14	RS14	8.5 x 31.5	1, 2, 4, 6, 10, 16, 20
RO14A	RS14A	8.5 x 23	1, 2, 4, 6, 10, 16, 20
RO15	RS15	10 x 38	2, 4, 6, 10, 16, 20, 25, 32
RO16	RS16	14 x 51	2, 4, 6, 10, 16, 20, 25, 32, 40, 50, 63
RO17	RS17	22 x 58	10, 16, 20, 25, 32, 40, 50, 63, 80, 100
RO21	RS21	DII	2, 4, 6, 8, 10, 13, 16, 20, 25
RO22	RS22	DIII	35, 40, 50, 63
RO26	RS26	D01	2-6, 10, 16
		D02	20, 25, 35, 50, 63
		D03	80, 100



RO26