

# DT26 Density Transmitter



DT26 Density Monitor

## Description

DT26 Density Transmitters are used to monitor SF<sub>6</sub> gas density in sealed tanks. It can provide multiple solutions to support new substations and the renovation and upgrading of existing substations.

## Features

- SF<sub>6</sub> gas remote density transmitter suitable for medium and high pressure system monitoring.
- All welded sensor structure, long - term stable sealing performance.
- RS485 bus communication (MODBUS RTU) .
- The EMC characteristics of the transmitter meet the requirements of IEC 61000-4-2 to IEC 61000-4-6 standards.
- Compact design.

## Application

- SF<sub>6</sub> Gas Insulated Switchgear (GIS)
- SF<sub>6</sub> Insulated Circuit Breakers
- SF<sub>6</sub> Insulated Pole-Mounted Switch
- SF<sub>6</sub> Insulated Transformer
- SF<sub>6</sub> Insulated Current Transformer or Voltage Transformer
- SF<sub>6</sub> Gas Insulated Busbar Systems
- SF<sub>6</sub> Insulated Inflatable Cabinet
- SF<sub>6</sub> Insulated RMU

## Options

- Pressure connection: M20 × 1.5(customizable)
- Measuring Medium: SF<sub>6</sub>, Air, N<sub>2</sub>, SF<sub>6</sub> + N<sub>2</sub> and other gases

## Technical Parameters

Measuring range	0 to 1.0MPa abs.or 0 to 0.2MPa abs.(customized)
Temperature measurement range	-40°C~ +80°C
Pressure measurement accuracy	±0.5% FS
Temperature measurement accuracy	±1°C
Density (P20) measurement accuracy	±1.0%FS
Degree of protection	IP65
Ambient conditions	-40° C to 70° C, relative humidity ≤ 95%RH
Leakage rate	≤ 1 × 10 <sup>-9</sup> Pa · m <sup>3</sup> /s (Helium leakage inspection)
Electrical connection	Hirschmann Connector
Weight	0.2kg

## Technical Parameters for Remote Module

Power supply	24V DC	EMC tests	IEC61000-4-2:level 4 IEC61000-4-3:level 3 IEC61000-4-4:level 4 IEC61000-4-5:level 4 IEC61000-4-6:level 3
Power consumption	< 0.5W		
Communication mode	RS485		
Protocol	ModBus RTU		
Baud rate	9600bps		

## Dimensions

