

BH(P 型)-0.66 型电流互感器

BH(P type)-0.66 type current transformer

适用范围 Scope of application

BHP-0.66 型电流互感器主要用于户内，供额定电压为 0.66kV 及以下，额定频率为 50Hz 的交流电路中作为电流、电能测量或继电保护用。产品为塑壳式电流互感器，广泛应用于成套柜体，其安装方法可采用母排固定和底板固定安装方法，适合任意方向安装。

符合标准：GB/T20840。

The BHP 0.66 type current transformer is mainly used indoors and is used in AC circuits with a rated voltage of 0.66kV and below and a rated frequency of 50Hz for current, energy measurement or relay protection. The product is a molded case current transformer, which is widely used in complete cabinet bodies. Its installation methods can adopt busbar fixation and base plate fixation installation methods, and it is suitable for installation in any direction.


Complies with the standard: GB/T20840.

正常工作条件及安装条件

Normal working conditions and installation conditions

- 安装场所：户内
- 环境温度：-5℃ ~ +40℃
- 环境湿度：相对湿度不大于 80%
- 海拔高度：不超过 1000m
- 大气条件：大气中无严重污秽
- Installation place: indoor
- Ambient temperature: -5℃ ~ +40℃
- Ambient humidity: The relative humidity is less than 80%
- Altitude: No more than 1000m
- Atmospheric conditions: no serious pollution in the atmosphere

型号及其含义 Model and its meaning



订货须知 Order instructions

用户在订货时，需提供以下信息：

- 1、产品型号及窗口宽度；
- 2、额定电流比；
- 3、额定输出及相应准确级；

例如：订货 LMK(DP)-0.66 型，窗口高度为 50mm，额定电流比 500/5A、额定输出 5VA、准确级 10P10 级的互感器。

订货代号为 LMK(DP)-0.66 中 50 500/5A 5VA 10P10 级。

- 4、如有特殊要求时，可与厂家协商定制。

When ordering, the user should provide the following information:

1. Product Model and window width;
2. Rated current ratio;
3. Rated output and the corresponding accuracy level;

For example: Order the LMK(DP)-0.66 type transformer with a window height of 50mm, a rated current ratio of 500/5A, a rated output of 5VA, and an accuracy class of 10P10.

The order code is LMK(DP)-0.66, 50 500/5A 5VA 10P10 grade.

4. If there are special requirements, can be customized with the manufacturer.





LMK4(BH)-0.66 50



LMK4(BH)-0.66 60



LMK4(BH)-0.66 80



LMK4(BH)-0.66 100



LMK4(BH)-0.66 130

型号 Model	电流比 (A) Current ratio	额定二次负荷 (VA) Rated secondary load			穿心匝数 Number of turns through the heart	外形及安装尺寸 Outline overall and installing dimensions
		10P5	10P10	10P15		
LMK(DP)-0.66 50	200/5	5			1	
	300/5	5	2.5		1	
	400/5	10	5	2.5	1	
	500/5	10	5	2.5	1	
	600/5	15	10	5	1	
	750/5	15	10	5	1	
LMK(DP)-0.66 60	800/5	15	10	5	1	
	400/5	10	5	2.5	1	
	500/5	10	5	2.5	1	
	600/5	10	5	2.5	1	
	750/5	10	5	2.5	1	
	800/5	10	5	2.5	1	
LMK(DP)-0.66 80	1000/5	10	10	5	1	
	1200/5	10	10	5	1	
	1500/5	10	10	5	1	
	600/5	10	5	2.5	1	
	750/5	10	5	2.5	1	
	800/5	10	5	2.5	1	
LMK(DP)-0.66 100	1000/5	10	10	5	1	
	1200/5	10	10	5	1	
	1500/5	10	10	5	1	
	2000/5	10	10	5	1	
	800/5	10	5	2.5	1	
	1000/5	10	10	5	1	
LMK(DP)-0.66 130	1200/5	10	10	5	1	
	1500/5	10	10	5	1	
	2000/5	10	10	5	1	
	2500/5	10	10	5	1	
	3000/5	10	10	5	1	
	4000/5	10	10	5	1	