

JSZV18-10、6R型电压互感器

JSZV18-10,6R voltage transformer

技术参数 Technical parameter

- 产品性能符合标准 GB20840.1-2010、GB20840.2-2013 和 IEC60044-2
- 额定绝缘水平 12/42/75、7.2/32/60kV
- 额定频率 50Hz 或 60Hz
- The product performance meets the standards GB20840.1-2010, GB20840.2-2013 and IEC60044-2.
- The rated insulation level is 12 / 42 / 75 、 7.2 / 32 / 60kV.
- Rated frequency 50Hz or 60Hz



产品型号 product model	额定电压比 (A) Voltage Ratio	准确级组合 Accurate level combination	准确级及额定输出 Accurate level and rated output			二次热极限输出 (VA) Secondary thermal limit output	重量 (kg) Weight
			0.2	0.5	1.0		
JSZV18-10R JSZV18-6R	10/0.1 6/0.1	0.2 0.5 1.0	30	50	150	2×400	60
JSZV18-10R JSZV18-6R	10/0.1/0.22 6/0.1/0.22	0.2 0.5 1.0	30	50	120	电源最大输出 2×400	

- 如用户要求的参数超出上表范围，可与我公司协商后确定。
- 配用熔断器型号为 XRNP □ -12、7.2 型，0.2、0.5A，50kA
- 配用肘型电缆头为 20kV 等级，美式 200A
- If the parameters required by the user exceed the scope of the above table, it can be determined after consultation with our company.
- The fuse model is XRNP □ -12, 7.2, 0.2, 0.5A, 50kA.
- Equipped with elbow type cable head for 20kV grade, American type 200A

外形图及安装尺寸 Outline and mounting dimensions

