



Interactive Flat Panel

RK3588 AI Chips

Interactive Panel is an all-in-one smart board supporting Android & Windows operating system, widely used in education and business to enhance learning and collaboration, allowing for more dynamic and engaging presentations.

The popular sizes are 65"75"86"98"110". It adopts infrared touch and zero-gap bonding technology, enhance the writing accuracy and faster respond that make a better user experience.



Official Website

4K

4K Original Panel

Zero-bonding makes writing more accurate, with A grade 4K touch panel.



Super Operation

Android 13.0/15.0,
Cortex-A76*4+A55*4
Octa-core CPU,
2.4GHz



Wireless Screen Share

Wireless screen share up to 9 devices (iOS, Android, Windows).



OTA Update

Providing OTA firmware and software feature updates.



Slide Lock Design

Slide lockable design to protect I/O ports, dust-proof and waterproof.

General Technical Parameters

LCD Panel	Screen Size	65 "	75 "	86 "
	Screen Type	DLED		
	Resolution	3840(H)×2160(V) (UHD)		
	Color	10 bit 1.07B		
	Active Size	1428.48*803.52mm	1649.66*927.93mm	1895.04*1065.96mm
	Brightness	≥450cd/m2		
	Contrast	≥5000:1 (according to panel brand)		
	Viewing Angle	178°		
	AG Glass	Tempered explosion-proof glass		
	Backlight Lifetime	>50000 hours		
Electrical performance	Max Power	≤250W	≤300W	≤400W
	Standby Power	≤0.5W		
	Voltage	110-240V(AC), 50/60Hz		
Touch	Touch Technology	IR touch; 20 points for Android and 50 points for Windows; HIB Free drive		
	Touch Items	Finger, Pen, any opaque objects		
	Response Speed	≤ 3ms		
	Operation System	Support Windows, Android, Mac OS, Linux		
System	Android 13.0/15.0, EDLA certified/GMS support			
Processor	CPU: RK3588, Cortex A76*4 and Cortex A55*4, 8 cores, 2.4GHz			
Stroage	RAM 8/16/32GB, ROM 128/256/512G			
Network	LAN/WiFi 2.4G+5G,WIFI 6, BT5.2			
Speakers	Power	20W*2 / 8Ω		
Working Environment	Working Temperature	0℃ ~ 40℃		
	Storage Temperature	- 20℃ ~ 60℃		
	Working Humidity	10%-90% non-condensing		
Accessories	Power cable*1; Remote control*1; Touch pen*1; QC&Warranty card*1;Wall brackets*1;			
Camera	In-built camera, 13/48M piexles; 4K resolution supported; 8-array microphone;AI auto voice tracking			
I/O Interfaces	Input Ports: HDMI, LAN(RJ45), AV in(mini),USB 3.0, USB2.0, RS232 , Touch USB, OPS Slot Output Ports: Coaxial, Earphone,HDMI out, Front Ports : HDMI-in,USB-C, Touch USB, USB 3.0			
Featured Apps	4K Whiteboard, Screen Share, Split Screen, Browser, PlayStore, Screen Lock, Annotation, FileTransfer, FileBrowser, Calender, Welcome Page, ScreenShot, Screen Record, Vote, AI Assistant ...			

OPS for Windows System (Optional)

OPS Type	OPS-C ; 80-Pin
Dimension	195*180*42mm
CPU	Intel I5-11th generation(I3/I5/I7 optional)
Memory	8G DDR4(Optional 8/16/32G)
Storage	256G SSD (128/256/512/1T G SSD)
Operating System	Pre-install Windows 11 Pro

Product Dimension

Items / Model No.	FC-65LED	FC-75LED	FC-86LED
Packing dimension	1570*1024*200mm	1795*1170*200mm	2040*1315*200mm
Product dimension	1485.88*908.43*103.7mm	1707.8*1033.41*103.7mm	1953.9*1172.51*103.7mm
Wall mount VESA	500*400mm	600*400mm	800*400mm
Weight(N.W/G.W)	32.16/39.3KG	44.2/54.2KG	54/67.8KG