



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

Product Specification

Customer: _____

Model Name: _____ H050BWQ40E3513-CT5B _____

Date: _____ 2023-10-24 _____

Version: _____ A0 _____

☒ **Preliminary Specification**

☐ **Final Specification**

For Customer's Acceptance

Approved by	Comment

Approved by	Reviewed by	Prepared by



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

Table of Contents

1 Record of Revision.....	3
2 General Specifications.....	4
3 Input/Output Terminals.....	5
4 Absolute Maximum Ratings.....	6
5 Electrical Characteristics.....	6
6 Interface Timing.....	8
7 Optical Characteristics.....	12
8 Environmental / Reliability Tests.....	15
9 Mechanical Drawing.....	16
10 Packing.....	17
11 Precautions For Use of LCD modules.....	18



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

1 Record of Revision

Rev	Issued Date	Description	Editor
A0	2023/10/24	First Release.	



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

2 General Specifications

Feature		Spec
Characteristics	Size	5 inch
	Resolution	480(horizontal)*272(Vertical)
	Interface	24bit-RGB
	Connect type	Connector
	Color Depth	16.7M
	Technology type	a-Si
	Pixel pitch (mm)	0.231 x 0.231
	Pixel Configuration	R.G.B. Vertical Stripe
	Display Mode	Normally White
	Driver IC	ST7257
	Viewing Direction	6 O'clock
	GSI Direction	12 O'clock
Mechanical	LCM+CTP (W x H x D) (mm)	120.7*76.3*5.03
	Active Area(mm)	110.88 x62.83
	With /Without TSP	With TSP
	Weight (g)	TBD
	LED Numbers	12 LEDs

Note 1: Viewing direction is follow the data which measured by optics equipment..

Note 2: Requirements on Environmental Protection: RoHS

Note 3: LCM weight tolerance: +/- 5%



3 Input/Output Terminals

No.	Symbol	Description
1	LEDK	Backlight LED Cathode
2	LEDA	Backlight LED Anode.
3	GND	Ground
4	VDD	Power supply
5~12	R0~R7	Data bus
13~20	G0~G7	Data bus
21~28	B0~B7	Data bus
29	GND	Ground
30	DCLK	Dot clock signal input. Latching input data at its rising edge.
31	DISP	Standby mode. Normally pulled high. DISP="1": Normally operation (Default) DISP="0": Timing controller, source driver will turn off ,all output are High-Z.
32	HSYNC	Horizontal sync input. Negative polarity.
33	VSYNC	Vertical sync input. Negative polarity..
34	DE	Data enable input. Active high to enable the input data bus under "DE Mode."
35	NC	No connected
36	GND	Ground
37	XR	The right side signal of TP
38	YD	The down side signal of TP
39	XL	The left side signal of TP
40	YU	The up side signal of TP



4 Absolute Maximum Ratings

Item	Symbol	MIN	MAX	Unit	Remark
Supply Voltage	V_{DD}	-0.3	5	V	
Operating Temperature	T_{OPR}	-20	70	°C	
Storage Temperature	T_{STG}	-30	80	°C	

5 Electrical Characteristics

5.1 Driving TFT LCD Panel

$T_a = 25^{\circ}\text{C}$

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Supply Voltage	V_{DD}	3.0	3.3	3.6	V	
Input Signal Voltage	Low Level	V_{IL}	GND	-	0.3x VDD	V
	High Level	V_{IH}	0.7x VDD	-	VDD	V
Output Signal Voltage	Low Level	V_{IL}	-	-	VSS+0.4	V
	High Level	V_{IH}	VDD-0.4	-	-	V

5.2 Driving Backlight

Item	Symbol	MIN	TYP	MAX	Unit	Remark
Forward Current	I_F	-	40	50	mA	
Forward Voltage	V_F	16.8	18	19.2	V	
Backlight Power consumption	W_{BL}	-	0.72	0.96	W	
LED Lifetime		-	25000	-	Hrs	

Note 1: Each LED : $I_F = 20\text{ mA}$, $V_F = 3.0\text{V}$.

Note 2: Optical performance should be evaluated at $T_a = 25^{\circ}\text{C}$ only.

Note 3: If LED is driven by high current, high ambient temperature & humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.





Figure : LED connection of backlight



5.3 Block Diagram






深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

6 Interface Timing

6.1 Timing relationship among DE, Source Output, Gate Output, Vcom

6.1 Output Timing Diagram



6.2 Parallel RGB Data Format




深圳市勋瑞光电科技有限公司


Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

Parallel RGB Mode Data format

(HV Mode)



(DE Mode)



Parallel RGB input timign table

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency	fclk	5	9	12	MHz
VSD period time	Tv	277	288	400	H
VSD display area	Tvd	272			H
VSD back porch	Tvb	3	8	31	H
VSD front porch	Tvfp	2	8	97	H
HSD period time	Th	520	525	800	DCLK
HSD display area	Thd	480			DCLK
HSD back porch	Thbp	36	40	255	DCLK
HSD front porch	Thfp	4	5	65	DCLK



Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency	fclk	-	27	-	MHz
VSD period time	Tv	277	288	400	H
VSD display area	Tvd	272			H
VSD back porch	Tvb	3	8	31	H
VSD front porch	Tvfp	2	8	97	H
HSD period time	Th	-	1728	-	DCLK
HSD display area	Thd	1440			DCLK

The top diagram illustrates the timing for DCLK, DE, and DATA. DCLK is a clock signal with period T_{clk} . DE is an enable signal with setup time T_{desu} and hold time T_{dehd} . DATA shows multiple data bursts labeled '1st data', '2nd data', and 'Last data'. The bottom diagram shows DCLK, Vsync, and Hsync. Vsync is a vertical sync signal with setup time T_{vsu} and hold time T_{vh} . Hsync is a horizontal sync signal with setup time T_{hsu} and hold time T_{hhd} . The total horizontal sync period is T_h . The vertical sync period is T_{vw} . The horizontal sync period is T_{vh} . The vertical sync period is T_{vsu} . The horizontal sync period is T_{hsu} .




深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.


6.4 Data Input Format

Vertical input timing




Serial 8-bit RGB Mode Data format

(HV Mode)



(DE Mode)



Parameters	Symbol	Min.	Typ.	Max.	Unit	Conditions
DCLK frequency	Fclk	24	27	30	MHz	
DCLK cycle time	Tclk	83	110	200	ns	
DCLK pulse duty	Tcwh	40	50	60	%	
Time from HSD to source output	Thso	-	13	-	DCLK	
Time from HSD to gate output	Thgo	-	27	-	DCLK	
Time from HSD to gate output off	Thgz	-	3	-	DCLK	
Time from HSD to VCOM	Thvc	-	12	-	DCLK	



7 Optical Characteristics

Items	Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing angles	θ_T	Center CR $\geq$ 10	-	45	-	Degree.	Note2
	θ_B		-	65	-		
	θ_L		-	65	-		
	θ_R		-	65	-		
Contrast Ratio	CR	$\Theta = 0$	400	500		-	Note1, Note3
Response Time	T_{ON}	25°C	-	15	30	ms	Note1, Note4
	T_{OFF}						
Color Chromaticity	W_X	Normal $\theta = \Phi = 0^\circ$	0.26	0.31	0.36	-	Note1, Note5
	W_Y		0.28	0.33	0.38	-	
Uniformity	U		80	-	-	%	Note1, Note6
NTSC				50		%	Note5
Luminance	L		250	300	-	CD/M2	Note1, Note7

Test Conditions:

1. IF= 20mA(one channel),the ambient temperature is 25.
2. The test systems refer to Note 1 and Note 2.


Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.




深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.



Note 2: Definition of viewing angle range and measurement system.
viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).



Note 3: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD is on the "White" state}}{\text{Luminance measured when LCD is on the "Black" state}}$$

“White state “:The state is that the LCD should driven by Vwhite.

“Black state”: The state is that the LCD should driven by Vblack.

Vwhite: To be determined Vblack: To be determined.

Note 4: Definition of Response time


The response time is defined as the LCD optical switching time interval between “White” state and “Black” state. Rise time (TON) is the time between photo detector output intensity changed from



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

90% to 10%. And fall time (TOFF) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

$$\text{Luminance Uniformity}(U) = L_{\min} / L_{\max} \times 100\%$$

L-----Active area length W----- Active area width




Fig. 2 Definition of uniformity

Lmax: The measured maximum luminance of all measurement position.

Lmin: The measured minimum luminance of all measurement position.

Note 7: Definition of Luminance :

Measure the luminance of white state at center point.





8 Environmental / Reliability Tests

No	Test Item	Condition	Remarks
1	High Temperature Operation	$T_s = +70^{\circ}\text{C}$, 96hrs	Note 1 IEC60068-2-2, GB2423. 2-89
2	Low Temperature Operation	$T_a = -20^{\circ}\text{C}$, 96hrs	Note 2 IEC60068-2-1 GB2423.1-89
3	High Temperature Storage	$T_a = +80^{\circ}\text{C}$, 96hrs	IEC60068-2-2 GB2423. 2-89
4	Low Temperature Storage	$T_a = -30^{\circ}\text{C}$, 96hrs	IEC60068-2-1 GB/T2423.1-89
5	High Temperature & Humidity Storage	$T_a = +60^{\circ}\text{C}$, 90% RH max, 96 hours	IEC60068-2-3 GB/T2423.3-2006
6	Thermal Shock (Non-operation)	-30°C 30 min ~ $+80^{\circ}\text{C}$ 30 min Change time: 5min, 20 Cycle	Start with cold temperature, end with high temperature IEC60068-2-14, GB2423.22-87
7	Electro Discharge (Operation) Static	$C=150\text{pF}$, $R=330\ \Omega$, 5 points/panel Air: $\pm 8\text{KV}$, 5 times; Contact: $\pm 4\text{KV}$, 5 times; (Environment: $15^{\circ}\text{C} \sim 35^{\circ}\text{C}$, 30% ~ 60%, 86Kpa ~ 106Kpa)	IEC61000-4-2 GB/T17626.2-1998
8	Vibration (Non-operation)	Frequency range: 10~55Hz, Stroke: 1mm Sweep: 10Hz~55Hz~10Hz 2 hours for each direction of X .Y. Z. (package condition)	IEC60068-2-6 GB/T2423.5-1995
9	Shock (Non-operation)	60G 6ms, $\pm X$, $\pm Y$, $\pm Z$ 3 times for each direction	IEC60068-2-27 GB/T2423.5-1995
10	Package Drop Test	Height: 80 cm, 1 corner, 3 edges, 6 surfaces	IEC60068-2-32 GB/T2423.8-1995

Note: 1. T_s is the temperature of panel's surface.

2. T_a is the ambient temperature of sample.

9 Mechanical Drawing



BACKLIGHT CIRCUIT DIAGRAM:
(If=40mA, VF=16.8V~19.2V)

PIN	定义	30	CLK
1	VSS	31	DISP
2	VDD	32	HSYNC
3	SCL	33	VSING
4	VSS	34	DE
5	SDA	35	NC
6	VSS	36	GND
7	[RST(有上拉电阻)]	37	NC/ XR
8	NC	38	NC/ YD
9	INT	39	NC/ XL
10	VSS	40	NC/ YU



- NOTES:
- DISPLAY TYPE: 5.0 INCH TFT /WHITE
 - BACKLIGHT: 12 CHIP WHITE LED, IN PARALLEL
 - OPERATING TEMP: -20° C~+70° C
 - STORAGE TEMP: -30° c~+80° c
 - RESOLUTION: 480 (RGB) x272
 - LCD IC:ST7257
 - Luminous instensity(9 AVG):250cd/m2 (MIN), 300cd/m2 (TYP)
 - Uniformity:80%(Min)
 - “() ”reference dimension. “*”critical dimension
 - Rohs Compliant
- CTP技术参数:
- IC型号:GT911 通道数: 10*15
 - 工作电压: 2.8V-3.3 V; 12C通讯电压2.8V-3.3 V
 - 透光率: ≥85%
 - 表面硬度: ≥6H
 - 工作环境: -30℃~+80℃, ≤90%RH
 - 储存环境: -30℃~+80℃, ≤90%RH
 - 未注尺寸公差按±0.2mm
 - 符合ROHS环保要求
 - ESD:接触放电4K, 空气放电8K

INTERFACE		RGB Interface		 深圳健华光电技术有限公司 Jianhua Photoelectric Technology (Shenzhen) CO.,LTD.			
		FPC Connector		MODEL NAME TFT Display Module			
VIEWING DIRECTION		12 o'clock		DWN		PART NO. H050BWQ40E3513-CT5B	
Gray Scale		6 o'clock		CHKD		REV. SHEET OF A0 1/1	
DIRECTION		PROJECTION		3RD ANGLE		TOLERANCE UNLESS SPECIFIED UNIT mm SCALE 1:1	



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

10 Packing

TBD



深圳市勋瑞光电科技有限公司

Xunrui Shenzhen Optoelectronics Technology Co., Ltd.

11 Precautions For Use of LCD modules

11.1 Handling Precautions

11.1.1. The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

11.1.2. If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

11.1.3. Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

11.1.4. The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

11.1.5. If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

- Isopropyl alcohol
- Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents

11.1.6. Do not attempt to disassemble the LCD Module.

11.1.7. If the logic circuit power is off, do not apply the input signals.

11.1.8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

11.1.8.1. Be sure to ground the body when handling the LCD Modules.

11.1.8.2. Tools required for assembly, such as soldering irons, must be properly ground.

11.1.8.3. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.

11.1.8.4. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

11.2 Storage Precautions

11.2.1. When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

11.2.2. The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature : 0℃ ~ 40℃ Relatively humidity: ≤80%

11.2.3. The LCD modules should be stored in the room without acid, alkali and harmful gas.

11.3 Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.