

VM-2206C / VM-2206D



Functional description:

1. Silent touch switch design;
2. Sturdy locking push-pull microphone boom design;
3. High-sensitivity microphone capsule design, with a pickup range up to 50 cm;
4. Red frosted indicator light design, indicating speaking status;
5. High-sensitivity touch buttons;
6. Supports multiple chairs online simultaneously;
7. Microphones can be configured with VIP microphone functionality via software, enabling more flexible and diverse usage to meet high-end requirements (requires simultaneous use with software).
8. Built-in 2W high-fidelity speaker;
9. Features a 3.5mm headphone jack;
10. Long-distance transmission will not affect sound quality in any way;
11. "Linear hand-in-hand" connection enables more convenient and reliable system connections, supporting ring-shaped connections.
12. Exceptional resistance to mobile phone RF interference;
13. The chairperson's microphone features a priority button that can mute the microphone of any delegate currently speaking.
14. Supports software and can connect to other central control devices via a 232 interface to enable centralized control;
15. The microphone features an 80×30 mm LED display capable of showing various microphone information and providing prompts for different operations.
16. Featuring a unique self-diagnostic function, this device automatically performs self-checks when paired with the software, simplifying pre-meeting preparation and ensuring reliable operation during conferences.

Technical specifications:

Screen size	80*30 (mm)
Pickup Distance	0-500mm
Audio Frequency Response	40Hz-19KHz
Sensitivity	-38dB±3dB
Signal-to-noise ratio	-80dB
Nonlinear distortion	< 0.3% (1KHz)
Weight	1.2Kg
Power Supply	DC24V
Microphone pole length	380mm
Dimensions (Length × Width × Height)	199 x 122 x 70 (mm)