



Functional description:

- 1. Extra-large silent switch design;
- 2. Sturdy locking push-pull microphone boom design;
- 3. High-sensitivity microphone capsule design, with a pickup range up to 50 cm;
- 4. Red frosted indicator light design, indicating speaking status;
- 5. Support for multiple chairs to be online simultaneously;
- 6. Long-distance transmission will not affect sound quality in any way;
- 7. "Linear hand-in-hand" connection for more convenient and reliable system integration;
- 8. Exceptional resistance to mobile phone RF interference;
- 9. The chairperson's microphone features a priority button that can mute the delegate unit currently speaking.
- 10. The microphone features an 80×30 mm LED display that shows various microphone information and provides prompts for different operations.
- 11. Features a unique self-diagnostic function that, when paired with the software, automatically performs device self-checks, simplifying pre-meeting preparation and ensuring more reliable operation during meetings.

Technical specifications:

Screen size	80*30 (mm)
Pickup Distance	zero to five hundred millimeters
Audio Frequency Response	40Hz-19KHz
Sensitivity	-42dB±3dB
Signal-to-noise ratio	-80dB
Harmonic distortion	< 0.3% (1KHz)
Power Supply	DC24V
Microphone pole length	370mm
Weight	0.85 kg
Dimensions (Length × Width × Height)	185 x 119 x 44 (mm)
Operating temperature	-20°C to 50°C