VM-2211C / VM-2211D





Functional description:

1. Extra-large silent switch design;
2. Sturdy locking push-pull microphone boom design;
3. High-sensitivity microphone capsule design, with a pickup range up to 50 cm;
4. Red frosted indicator light design, indicating speaking status;
5. Support for multiple chairs to be online simultaneously;
6. Long-distance transmission will not affect sound quality in any way;
7. "Linear hand-in-hand" connection for easier and more reliable system integration;
8. Supports daisy-chain connection; if the main microphone cable breaks in the middle, it will not affect usage.
9. Exceptional resistance to mobile phone RF interference;
10. The chairperson's microphone features a priority button that can mute the microphone of any delegate currently speaking.
11. The microphone features an 80×30 LED display capable of showing multiple indicators, including microphone ID numbers and speaking time timers.
12. Featuring a unique self-diagnostic function, this device automatically performs self-checks when paired with the software, simplifying pre-meeting preparation and ensuring reliable operation during meetings.
13. Supports transmission via network cable or 8-core cable (network cable requires a dedicated connection box);
14. Microphone waterproof rating: IPV5;
15. Can be connected to a dedicated recording module to enable recording functionality;
16. Built-in sensitivity adjustment allows independent sensitivity tuning for any individual microphone, ensuring maximum audio output gain for the conference room system.
17. Supports visual tracking;
18. Supports software and can connect to other central control devices via a 232 interface to enable centralized control;

Technical specifications:

Screen size	80*30 (mm)
Pickup Distance	0-500 mm
Audio Frequency Response	40Hz-19KHz
Sensitivity	-42dB±3dB
Signal-to-noise ratio	-80dB
Harmonic distortion	< 0.3% (1KHz)
Power Supply	DC24V
Mic Rod Length	370mm
Weight	0.95 kg
Dimensions (Length × Width × Height)	182 x 119 x 57 (mm)
Operating Temperature	-20°C to 50°C