VM-2213C / VM-2213D



Functional description:

1. Extra-large silent switch design;
2. Sturdy locking push-pull microphone boom design;
3. When speaking, both the red light ring on the microphone boom and the red indicator light on the microphone base will illuminate simultaneously.
4. Features two red LED displays showing the microphone address.
5. High-sensitivity microphone capsule design with a pickup range up to 50 cm;
6. Supports multiple chairs online simultaneously;
7. Supports video tracking;
8. Selectable modes include First-Come-First-Served Speaking Mode and Free Discussion Mode. Computer-controlled support includes Queue Mode, Computer-Permitted Mode, Free Discussion Mode, and Timed Mode.
9. Long-distance transmission will not affect sound quality in any way;
10. Built-in 3W high-fidelity speaker for conference amplification;
11. Features a built-in 3.5mm headphone output jack;
12. Hand-in-hand connection ensures greater system reliability;
13. A single 10-meter extension cable can support up to 30 microphones.
14. Exceptional resistance to mobile phone interference;
15. The chairperson's microphone features a priority button that can mute the microphone of any delegate currently speaking.

Technical specifications:

Pickup Distance	0-50 CM
Audio Output Level	<0dB, with a typical value of 200 mV when speaking at a distance of 20 cm
Output Frequency Response	100Hz-18KHz
Signal-to-noise ratio	≥80dB
Power Supply	DC24V
System sensitivity	-38dB±2dB
Mic Rod Length	370mm
Weight	0.75kg
Dimensions (Length × Width × Height)	157 x 119 x 52 (mm)