



Function Description:

1. Line Key: Fixed line keys displayed on the main screen.
2. Supports G.722 and Opus voice coding to handle various audio applications.
3. Used to realize two-way voice intercom with our company' s intercom terminals and network microphones.
4. Supports external EHS wireless headsets.
5. Adapts to 10/100/1000 Mbps network ports, providing high-speed network transmission and supporting PoE power supply.
6. Two desktop mounting angles: 45° and 50°.
7. Cost-effective with a modern, minimalist design and high-resolution TFT color display for an excellent visual experience.
8. Compatible with mainstream SIP-based IP PBX / Softswitch / IMS platforms, such as Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya, etc.

Technical specifications:

Model	VP-8012
Screen	2.8-inch (320x240) color screen
Power Input	PoE power supply (IEEE 802.3at standard)
Keyboard	37 keys
HD Handset (RJ9)	x1
Standard RJ9 Handset Cord	x1
1.5M CAT.5E Network Cable	x1
Phone Stand	x1
Status Indicator	x1 (red)
RJ9 Interfaces (x2)	1 for handset, 1 for headset
RJ45 Interfaces (x2)	1 for network, 1 for PC (network bridge mode)
Power Consumption	Standby: 0.9~1.58W, Peak: 2.8~3.34W
Operating Temperature	0°C - 45°C
Relative Humidity	10~95%
Installation Method	Desktop
Dimensions	(Angle 1): 169x186.3x174.5 mm, (Angle 2): 169x177.6x183.7 mm
Net Weight	0.7kg