750°C High-Temp Copper & Nylon Fast Connector，AWG 8 #，CE8，Nylon-insulated

- **The terminal features a fully insulated sleeve that completely covers the conductive parts, effectively preventing accidental contact, short circuits, and electrical hazards. This makes it ideal for safe use in dense wiring environments.**
- **Designed with a plug-in structure, the terminal allows quick connection and disconnection without the need for complex tools, greatly improving installation efficiency and simplifying maintenance work.**
- **The crimped metal core ensures a firm and stable connection, while the tight-fitting design provides excellent resistance to vibration. The protective sleeve also helps block dust and moisture, extending the service life.**



Product Classification

Model	CE8
Part Number	-
Detail Description	750°C High-Temp Copper & Nylon Fast Connector，AWG 8 #，CE8，Nylon-insulated

General Specifications

Color Code	Nature

Dimensions



Inner Diameter (d)	0.21	in |	5.3	mm
Outer Diameter (D)	0.56	in |	14.3	mm
Overall Length (L)	1.09	in |	27.7	mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: JAN 16, 2026
Public

Electrical Specifications

Rating - Maximum Voltage	35KV

Environmental Specifications

Operating Temperature	-40 °C to +750°C (-40 °F to +1382 °F)
Storage Temperature	-40 °C to +80°C (-40 °F to +176 °F)

Packaging and Weights

Included	Butt Splice
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.