DATASHEET

NYLON-FLAG FEMALE INSULATED JOINT TERMINALS，AWG 16-14 #，Without hole，FLDNY 2-250-2-PS，Continuous，Blue

- **Copper cable lugs are designed for connecting copper cables, coils and Bus-bars**
- **Continuous terminals improve automated production efficiency with stable feeding and consistent crimping performance.**
- **Compact structure and secure crimping provide vibration-resistant and safe electrical connections.**
- **Insulation is locked in place, will not twist off, maintaining proper dielectric values.**
- **"colour code" colored sheath help choose the right connector.**



Product Classification

Model	FLDNY 2-250-2-PS
Part Number	-
Detail Description	NYLON-FLAG FEMALE INSULATED JOINT TERMINALS，AWG 16-14 #，Without hole，FLDNY 2-250-2-PS，Continuous，Blue

General Specifications

Color Code	Blue
Material	Brass
Tongue Type	Female Insulated Joint
Tongue Angle	Straight
Surface	Tin-plated

Dimensions



TAB SIZE	0.8*6.35
Overall Width (W)	0.30 in | 7.6 mm
Overall Length (L)	0.61 in | 15.4 mm
Outer Diameter (D)	0.24 in | 6.0 mm
Inner Diameter (d)	0.09 in | 2.3 mm
Barrel Length (B)	0.30 in | 7.6 mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: JAN 16, 2026
Public

Electrical Specifications	
Rating - Maximum Voltage	600V
Environmental Specifications	
Operating Temperature	-40 °C to +105°C (-40 °F to +221 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.