COPPER ALUMINUM TERMINALS，AWG 4 #，GTL-25，Butt Splice

- **Resolve the copper-aluminum potential difference**
- **Ensure safe copper–aluminum transition，Provide a reliable electrical connection between circuit,Offer low contact resistance to reduce heat generation and power loss.**
- **The absence without inspection window prevents the entry of water or moisture into the crimped joint making these terminals suitable for outdoor applications.**
- **The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.**
- **Manufactured from seamless tubing;a high quality design with no seams to split**




Product Classification

Model	GTL-25
Detail Description	COPPER ALUMINUM TERMINALS，AWG 4 #，GTL-25，Butt Splice

General Specifications

Material	Copper Aluminum
Tongue Angle	Straight
Surface	Pickling

Dimensions



Outer Diameter-AL (D)	0.47	in |	12.0	mm
Inner Diameter-AL (d)	0.28	in |	7.0	mm
Outer Diameter-CU (D1)	0.39	in |	10.0	mm
Inner Diameter-CU (d1)	0.23	in |	5.8	mm
Barrel Length-AL (L1)	1.30	in |	33.0	mm
Barrel Length-CU (L2)	1.18	in |	30.0	mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: JAN 16, 2026
Public

Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Butt Splice
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.