NON-INSULATED RING-90° TERMINALS，AWG 2 # ，one hole 1/4 ”，R38-6/90

- **Copper cable lugs are designed for connecting copper cables, coils and Bus-bars**
- **Brazed seam provides a stronger barrel design, minimizes any possible splitting and eliminated folding.**
- **Electro-tin plated for durable, long lasting resistance to corrosion.**
- **Ring tongue design provides a secure termination under screw head that cannot be removed without the complete removal of the screw.**
- **90 degree standard barrel for limited space applications.**




Product Classification

Model	R38-6/90
Part Number	-
Detail Description	NON-INSULATED RING-90° TERMINALS，AWG 2 # ，one hole 1/4 ”，R38-6/90

General Specifications

Material	Copper
Tongue Type	Ring
Tongue Angle	90° degree
Surface	Tin-plated

Dimensions



STUD SIZE	1/4	in	6.0	mm
Bolt Size (E)	0.25	in	6.4	mm
Tongue Width (W)	0.60	in	15.3	mm
Tongue Length (C)	0.79	in	20.0	mm
Barrel Length (B)	0.55	in	14.0	mm
Outer Diameter (D)	0.51	in	13.0	mm
Inner Diameter (d)	0.38	in	9.6	mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: JAN 16, 2026
Public

Electrical Specifications	
Rating - Maximum Voltage	35kV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.