DATASHEET

NYLON-INSULATED SPADE TERMINALS FUNNEL ENTRY，AWG 8#，Without hole，SNY8-10，Nylon-insulated，Red，Funnel entry

- **Copper cable lugs are designed for connecting copper cables, coils and Bus-bars**
- **Fork tongue design for faster installation.**
- **The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.**
- **Insulation is locked in place, will not twist off, maintaining proper dielectric values.**
- **"colour code" colored sheath help choose the right connector.**



Product Classification

Model	SNY8-10
Part Number	-
Detail Description	NYLON-INSULATED SPADE TERMINALS FUNNEL ENTRY，AWG 8#，Without hole，SNY8-10，Nylon-insulated，Red，Funnel entry

General Specifications

Color Code	Red
Material	Copper
Tongue Type	Spade
Tongue Angle	Straight
Surface	Tin-plated

Dimensions



STUD SIZE	3/8	in	10.0	mm
Bolt Size (E)	0.41	in	10.5	mm
Tongue Width (W)	0.59	in	15.0	mm
Overall Length (L)	1.42	in	36.0	mm
Barrel Length (B)	0.63	in	16.0	mm
Outer Diameter(D)	0.31	in	8.0	mm
Inner Diameter (d)	0.18	in	4.5	mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +105°C (-40 °F to +221 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.