DATASHEET

COPPER TUBE TERMINALS，AWG 12-10 #，one hole #10 ”，TLK6-5，standard barrel，without inspection window，thicken

- **Copper cable lugs are designed for connecting copper cables, coils and Bus-bars**
- **Electro-tin plated for durable, long lasting resistance to corrosion.**
- **The reinforced tongue structure improves mechanical strength and resists deformation under high tightening force.**
- **The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.**




Product Classification

Model	TLK6-5
Part Number	-
Detail Description	COPPER TUBE TERMINALS，AWG 12-10 #，one hole #10 ”，TLK6-5，standard barrel，without inspection window，thicken

General Specifications

Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	Without inspection window

Dimensions



STUD SIZE	#10	in	5.0	mm
Bolt Size (E)	0.22	in	5.5	mm
Tongue Width (W)	0.39	in	10.0	mm
Overall Length (L)	1.08	in	27.5	mm
Outer Diameter (D)	0.26	in	6.5	mm
Inner Diameter (d)	0.14	in	3.5	mm
Barrel Length (B)	0.35	in	9.0	mm

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: JAN 16, 2026
Public

Electrical Specifications

Rating - Maximum Voltage	35kV

Environmental Specifications

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	- lb | - kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

©ZLX TERMINALS Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.