
Hinew Electric Co., Ltd.


Fuseholder H3-45A/B

PCB mount

Shock-Safe Fuseholder, 5*20 6.3 x 32 mm, Slot



H3-45A



H3-45B

250VAC 2.5W/10A

Description

- Quick-conntect or solder terminals

References

Weblinks

pdf, General Product Information, Approvals, RoHS, CHINA-RoHS,

Standards

IEC60127-6

UL4248-1/UL512

GB9364.6

Approvals

- VDE Certificate Number: 134125


' UL File Number: E239034


Technical Data


Shocksafe Category	PC2	Soldering Methods	Iron
Fuse-Link	A:5*20mm B:6*30mm	Solderability	350℃ / 2sec acc. to IEC 60068-2-20, Test Ta, method 2
Mounting	pcb installation		
Terminal	Solder or Quick-Connect 5.0 x 0.5 mm	Resistance to Soldering Heat	350℃ / 10sec acc. to IEC 60068-2-20, Test Tb, method 2
Rated Voltage	250VAC		
Rated Current	10A (VDE), 10A (UL)	Contact Resistance	< 5mΩ at 20 mV
Rated Power Acceptance IE	2.5W / 10A @ Ta 23℃	Dielectric Strength	> 3kV between L-N
	Admissible power acceptance at hig		> 4kV between L/N-PE
	her ambient temperature see derating		(50Hz; 1 min)
	curves	Impulse Withstand Voltage	> 4kV between L-N
Degree of Protection			> 6kV between L/N-PE
Protection Class	Suitable for appliances with protection	Insulation Resistance	> 10MΩ between L-N
	class 1 or 2 acc. to IEC 61140		> 100MΩ between L/N-PE
Admissible Ambient Air Tem	-40℃to85℃		(500VDC; 1 min)
Climatic Category	40/085/21 acc. to IEC 60068-1	Overvoltage Category	I - III acc. to IEC 60664-1
Material: Socket	Thermoplastic, black, UL 94V-0	Pollution Degree	1 - 3 acc. to IEC 60664-1
Material: Terminals	Nickel plated copper		
Unit Weight (Socket/Cap)	5.5 g / 3.22 g		
Storage Conditions	0℃ to 60℃, max. 70% r.h.		
Product Marking	Type, Voltage, Current, Approvals		


Hinew Electric Co., Ltd.

Abmessungen










H3-45A H3-45B

Mounting holes

Derating Curves



Variants

多个产品可拼接一起

Packaging Unit

Bulk(100pcs)

Required Accessory