V_{CE} = 4500 V
I_C = 800 A



ABB HiPak

IGBT Module

5SNA 0800J450300

Doc. No. 5SYA1402-04 05-2016

- **Ultra low-loss, rugged SPT+ chip-set**
- **Smooth switching SPT+ chip-set for good EMC**
- **Industry standard package**
- **High power density**
- **AlSiC base-plate for high power cycling capability**
- **AlN substrate for low thermal resistance**
- **Improved high reliability package**
- **Recognized under UL1557, File E196689**



Maximum rated values [1]

Parameter	Symbol	Conditions	min	max	Unit
Collector-emitter voltage	V_{CES}	V_{GE} = 0 V		4500	V
DC collector current	I_C	T_c = 85 °C		800	A
Peak collector current	I_{CM}	t_p = 1 ms, T_c = 85 °C		1600	A
Gate-emitter voltage	V_{GES}		-20	20	V
Total power dissipation	P_{tot}	T_c = 25 °C, per switch (IGBT)		7200	W
DC forward current	I_F			800	A
Peak forward current	I_{FRM}			1600	A
Surge current	I_{FSM}	V_R = 0 V, T_{vj} = 125 °C, t_p = 10 ms, half-sinewave		6000	A
IGBT short circuit SOA	t_{psc}	V_{CC} = 3400 V, $V_{CEM\,CHIP} \leq$ 4500 V $V_{GE} \leq$ 15 V, $T_{vj} \leq$ 125 °C		10	µs
Isolation voltage	V_{isol}	1 min, f = 50 Hz		10200	V
Junction temperature	T_{vj}			150	°C
Junction operating temperature	$T_{vj(op)}$		-50	125	°C
Case temperature	T_c		-50	125	°C
Storage temperature	T_{stg}		-50	125	°C
Mounting torques [2]	M_s	Base-heatsink, M6 screws	4	6	Nm
	M_{t1}	Main terminals, M8 screws	8	10	
	M_{t2}	Auxiliary terminals, M4 screws	2	3	

[1] Maximum rated values indicate limits beyond which damage to the device may occur per IEC 60747
[2] For detailed mounting instructions refer to ABB Document No. 5SYA2039

ABB Switzerland Ltd, Semiconductors reserves the right to change specifications without notice.

IGBT characteristic values [3]

Parameter	Symbol	Conditions		min	typ	max	Unit
Collector (-emitter) breakdown voltage	$V_{(BR)CES}$	V_{GE} = 0 V, I_C = 10 mA, T_{vj} = 25 °C		4500			V
Collector-emitter [4] saturation voltage	$V_{CE\ sat}$	I_C = 800 A, V_{GE} = 15 V	T_{vj} = 25 °C		2.6	2.9	V
			T_{vj} = 125 °C		3.55	3.9	V
Collector cut-off current	I_{CES}	V_{CE} = 4500 V, V_{GE} = 0 V	T_{vj} = 25 °C			8	mA
			T_{vj} = 125 °C			80	mA
Gate leakage current	I_{GES}	V_{CE} = 0 V, V_{GE} = ±20 V, T_{vj} = 125 °C		-500		500	nA
Gate-emitter threshold voltage	$V_{GE(TO)}$	I_C = 160 mA, V_{CE} = V_{GE}, T_{vj} = 25 °C		4.5		6.5	V
Gate charge	Q_{ge}	I_C = 800 A, V_{CE} = 2800 V, V_{GE} = -15 V .. 15 V			5.91		µC
Input capacitance	C_{ies}	V_{CE} = 25 V, V_{GE} = 0 V, f = 1 MHz, T_{vj} = 25 °C			80		nF
Output capacitance	C_{oes}				4.01		
Reverse transfer capacitance	C_{res}				1.72		
Internal gate resistance	R_{Gint}				1.75		Ω
Turn-on delay time	$t_{d(on)}$	V_{CC} = 2800 V, I_C = 800 A, R_G = 2.2 Ω, C_{GE} = 150 nF, V_{GE} = ±15 V, L_σ = 150 nH, inductive load	T_{vj} = 25 °C		870		ns
			T_{vj} = 125 °C		860		
Rise time	t_r		T_{vj} = 25 °C		150		ns
			T_{vj} = 125 °C		170		
Turn-off delay time	$t_{d(off)}$	V_{CC} = 2800 V, I_C = 800 A, R_G = 2.2 Ω, C_{GE} = 150 nF, V_{GE} = ±15 V, L_σ = 150 nH, inductive load	T_{vj} = 25 °C		2070		ns
			T_{vj} = 125 °C		2220		
Fall time	t_f		T_{vj} = 25 °C		510		ns
			T_{vj} = 125 °C		600		
Turn-on switching energy	E_{on}	V_{CC} = 2800 V, I_C = 800 A, R_G = 2.2 Ω, C_{GE} = 150 nF, V_{GE} = ±15 V, L_σ = 150 nH, inductive load	T_{vj} = 25 °C		1850		mJ
			T_{vj} = 125 °C		2580		
Turn-off switching energy	E_{off}	V_{CC} = 2800 V, I_C = 800 A, R_G = 2.2 Ω, C_{GE} = 150 nF, V_{GE} = ±15 V, L_σ = 150 nH, inductive load	T_{vj} = 25 °C		3150		mJ
			T_{vj} = 125 °C		3780		
Short circuit current	I_{SC}	t_{psc} ≤ 10 µs, V_{GE} = 15 V, T_{vj} = 125 °C, V_{CC} = 3400 V, $V_{CEM\ CHIP}$ ≤ 4500 V			3500		A
Module stray inductance	$L_{\sigma\ CE}$				27		nH
Resistance, terminal-chip	$R_{CC'+EE'}$		T_C = 25 °C		0.11		mΩ
			T_C = 125 °C		0.15		

[3] Characteristic values according to IEC 60747 – 9
[4] Collector-emitter saturation voltage is given at chip level

Diode characteristic values [5]

Parameter	Symbol	Conditions		min	typ	max	Unit
Forward voltage [6]	V_F	I_F = 800 A	T_{vj} = 25 °C		3.2	3.7	V
			T_{vj} = 125 °C		3.5	4	
Reverse recovery current	I_{rr}	V_{CC} = 2800 V, I_F = 800 A, V_{GE} = ±15 V, R_G = 2.2 Ω, C_{GE} = 150 nF, L_σ = 150 nH inductive load	T_{vj} = 25 °C		1110		A
			T_{vj} = 125 °C		1180		
Recovered charge	Q_{rr}		T_{vj} = 25 °C		730		µC
			T_{vj} = 125 °C		1120		
Reverse recovery time	t_{rr}		T_{vj} = 25 °C		1150		ns
			T_{vj} = 125 °C		1650		
Reverse recovery energy	E_{rec}		T_{vj} = 25 °C		1140		mJ
			T_{vj} = 125 °C		1880		

[5] Characteristic values according to IEC 60747 – 2
[6] Forward voltage is given at chip level

Package properties [7]

Parameter	Symbol	Conditions	min	typ	max	Unit
IGBT thermal resistance junction to case	$R_{th(j-c)IGBT}$				0.014	K/W
Diode thermal resistance junction to case	$R_{th(j-c)DIODE}$				0.028	K/W
IGBT thermal resistance case to heatsink [2]	$R_{th(c-s)IGBT}$	IGBT per switch, λ grease = 1W/m x K		0.013		K/W
Diode thermal resistance case to heatsink [7]	$R_{th(c-s)DIODE}$	Diode per switch, λ grease = 1W/m x K		0.027		K/W
Partial discharge extinction voltage	V_e	f = 50 Hz, $Q_{PD} \leq$ 10pC (acc. to IEC 61287)	5100			V
Comparative tracking index	CTI		≥ 600			

[2] For detailed mounting instructions refer to ABB Document No. 5SYA2039

Mechanical properties [7]

Parameter	Symbol	Conditions		min	typ	max	Unit
Dimensions	L x W x H	Typical , see outline drawing		130 x 140 x 48			mm
Clearance distance in air	d_a	according to IEC 60664-1 and EN 50124-1	Term. to base:	40			mm
			Term. to term:	26			
Surface creepage distance	d_s	according to IEC 60664-1 and EN 50124-1	Term. to base:	64			mm
			Term. to term:	56			
Mass	m				1010		g

[7] Package and mechanical properties according to IEC 60747 – 15

Electrical configuration



Outline drawing [2)]



Note: all dimensions are shown in mm

[2)] For detailed mounting instructions refer to ABB Document No. 5SYA2039

This is an electrostatic sensitive device, please observe the international standard IEC 60747-1, chap. IX.

This product has been designed and qualified for Industrial Level.



Fig. 1 Typical on-state characteristics, chip level



Fig. 2 Typical transfer characteristics, chip level



Fig. 3 Typical output characteristics, chip level



Fig. 4 Typical output characteristics, chip level



Fig. 5 Typical switching energies per pulse vs collector current



Fig. 6 Typical switching energies per pulse vs gate resistor



Fig. 7 Typical switching times vs collector current



Fig. 8 Typical switching times vs gate resistor



Fig. 9 Typical capacitances vs collector-emitter voltage



Fig. 10 Typical gate charge characteristics



Fig. 11 Turn-off safe operating area (RBSOA)



Fig. 12 Typical reverse recovery characteristics vs forward current



Fig. 13 Typical reverse recovery characteristics vs di/dt



Fig. 14 Typical diode forward characteristics, chip level



Fig. 15 Safe operating area diode (SOA)



Fig. 16 Thermal impedance vs time

Analytical function for transient thermal impedance:

$$Z_{th\,(j\text{-}c)}(t) = \sum_{i=1}^{n} R_i \left(1 - e^{-t/\tau_i}\right)$$

	i	1	2	3	4	5
IGBT	R_i(K/kW)	9.54	3.17	1.56		
	τ_i(ms)	193	21.4	2.78		
DIODE	R_i(K/kW)	18.7	6.56	3.23		
	τ_i(ms)	192	22.6	3.1		

Related documents:

5SYA 2042 Failure rates of HiPak modules due to cosmic rays
5SYA 2043 Load – cycle capability of HiPaks
5SYA 2045 Thermal runaway during blocking
5SYA 2053 Applying IGBT
5SYA 2058 Surge currents for IGBT diodes
5SYA 2093 Thermal design of IGBT modules
5SYA 2098 Paralleling of IGBT modules
5SZK 9111 Specification of environmental class for HiPak Storage
5SZK 9112 Specification of environmental class for HiPak Transportation
5SZK 9113 Specification of environmental class for HiPak Operation (Industry)
5SZK 9120 Specification of environmental class for HiPak

We reserve the right to make technical changes or to modify the contents of this document without prior notice.
We reserve all rights in this document and the information contained therein. Any reproduction or utilization of this document or parts thereof for commercial purposes without our prior written consent is forbidden.
Any liability for use of our products contrary to the instructions in this document is excluded.

ABB Switzerland Ltd
Semiconductors
Fabrikstrasse 3
CH-5600 Lenzburg, Switzerland

Telephone +41 (0)58 586 1419
Fax +41 (0)58 586 1306
Email abbsem@ch.abb.com
Internet www.abb.com/semiconductors

Doc. No. 5SYA1402-04 05-2016