L3000 Specialized Truck

SHACMAN



Wechat/Whatsapp: +86 13572928086 (BOb)

Drive			4×2
GVW (t)			12-18
Main configuration	Cab	Type	Standard
		Suspension	Front fixed rear hydraulic suspension
		Air conditioner	Electric air conditioning
	Engine	Model	WP6, WP7, ISD
		Emission standard	EURO Ⅲ-EURO V
		Rated power (hp)	210-300
		Torque Range (N·m)	650-1160
	Transmission	Model	MT(8/9)
		Torque Range (N·m)	850-1190
	Axle	Front axle	4.8t
		Rear axle	10t single-stage
	Chassis	Dimension(mm)	870×250(7+4)
		Wheel base (mm)	3600/3800/4000/4500
		Wheel overhang(mm)	2300
		Fuel tank	200L
		Tire	10.00R20
		Suspension	Leaf spring suspension
	Oil Tanker (m³)/Garbage Container(m³)		10-12
Applicable condition	Applicable road condition		Urban roads
Basic equipment			Electric window lifter, LED daytime running lights, central locking (dual remote control), fixed pedals, spare tire frame, aluminum alloy gas cylinder
Other configurations			Deflectors, air main seat, electric flip, third seat

Engine					
Emission Standards	Model	Engine Capacity (L)	Power (Ps)	Maximum Torque (N·m)	Rated Speed (rpm)
Euro V	WP7	7.47	240-270	1050-1160	2100-2300
	ISD	6.7	245-300	950-1100	2500
	ISDe	6.7	210	800	2500
Euro Ⅱ	WP6	6.8	180-240	680-860	2300

Transmission					
Shift Mode	Model	Gear Position	Torque Range (N·m)	Overdrive Gear/Direct Drive Gear	Speed ratio range
MT	S8MO	8/2	850	Overdrive	9.65-0.74; R9.80/2.27
	S8MO	8/2	850	Overdrive	10.36-0.79; R10.53/2.44
	S9MO	9/1	1190	Overdrive	11.02-0.73; R11.52