

### 技术规格 Technical specification

ITEM	单位 UNIT	技术规格 Specifications	
Operating mass 操作重量	kg	820	
Length 总长	mm	2300	
Width 总宽	mm	1300	
Height 总高	mm	850	
Approach angle 接近角	°	25	
Departure angle 离去角	°	20	
Gradeability 爬坡能力	%	46	
Remote control distance 遥控距离	m	>50	
Rated output 额定功率	HP	28	
Rated speed 额定转速	rpm	2200	
Max. Traction 最大牵引力	kN	/	
Track shoe gauge 轨距	mm	752	
Track grounding length 履带接地长度	mm	1050	
Standard track width 标准履带宽度	mm	180	
Ground pressure 接地比压	kpa	21	
Min. ground clearance 最小离地间隙	mm	145	
Min. turning radius 最小转弯半径	mm	1500	
Supporting wheel 支重轮	PCS	12	
Guide wheel assy 导向轮	PCS	2	
Transmission type 变速箱形式		Mechanical shift	
Gear shift position 档位		(3F+1R) x 2	
Speed 行驶速度	低速 Low	km/h	F: 0.55/0.8/1.2 R: 0.5
	高速 High	km/h	F: 2.25/3.2/5.0 R: 1.7
System pressure 工作系统压力	MPa	12	
Model of oil pump 工作泵型号	-	CBW-F304	
Pump flow 工作泵流量	ml/r	4	
System voltage 系统电压	V	12	
Front counterweight 前置配重(optional)	kg	90	
Oil Capacity 加油量	Fuel 燃油	L	24
	Engine oli 机油	L	/
	Transmission oil 变速箱油	L	/
	Hydraulic oil 液压油	L	/
	Coolant 冷却剂	L	Water

\* Subject to change without notice. Illustrations in this article are not necessarily standard for this model.

### 国机重工集团国际装备有限公司

SINOMACH-HI INTERNATIONAL EQUIPMENT CO., LTD.

Add: No.898 West Huang He Road, Changzhou city, Jiangsu Province, China

PC: 213136

Tel: 86-519-86781288 86752400

Fax: 86-519-86781387

Http://www.sinomachhiglobal.com

E-mail: sales@changlin.com.cn service@changlin.com.cn



# CT120

SINOMACH-HI International Equipment Co., Ltd.

### Optional Attachment



- The first one adopts special gearbox for crawler tractor
- Adopting industrial grade remote control and hydraulic parts of engineering machinery
- It adopts century brand Changchai T35 energy-saving heavy-duty diesel engine



国机重工集团国际装备有限公司  
SINOMACH-HI International Equipment Co., Ltd.