

SINOMACH

Equip the world and create value



Tire asphalt paver **GYA6000L(B)**

MAIN FEATURES

- Dongfeng Cummins water-cooled engine.
- Equipped with hydraulic drive motor for front wheel -GYA6000LB.
- Rear drive axle is gantry type,consisting of two speed transmission plus reducers.
- Closed hydraulic travel system,stepless speed shift,variable displacement control which is both agile and dependable.
- Hydraulic pump with electronic proportional control.
- Hydraulic extension of mangles and fuel heating system.

GYA6000L(B) Tire asphalt paver

Main technical parameter

No	Item	GYA6000L(B)
1	Basic width	2.5m
2	Max.with	6.0m
3	Max.thickness	200mm
4	Theoretical productivity	400t/h
5	Capacity of the bunker	13t
6	Working speed	0-15m/min
7	Hopper capacity	±0.02%
8	Tamping frequency	-1%/+3%
9	Type of drive	4×2 (6×6)

Engine

Mode.....4BTA3.9
 Manufacturer.....Cummins
 Rated speed.....2200r/min
 Rated power.....93Kw

Operation control system

Favorable exchange interface between machines and driver;
 Humanized design operation table can be moved to right-left,the seat could be adjusted and moved beyond the machine,so driver can observe the paving condition at anytime.

Traveling system

Gas heating achieves a quick temperature rise up;
 The strong tamper can improve degree of compaction of paving materials;
 Equip with ultrasonic leveling adjuster to reach optimum paving leveling.

Operation control system

Favorable exchange interface between machine and driver;
 Humanized design operation table can be moved to right-left,the seat could be adjusted and moved beyond the machine,so driver can observe the paving condition at anytime.

Traveling system

Length.....6290mm
 Width.....2690mm
 Height(with the cab).....3600mm
 weight.....16t(17t)

Conveyor and auger

Two independent hydraulic systems drive right-left helical material distributor, full hydraulic helical material distributor;
 its height is adjustable and suitable for any working condition.
 Two independent hydraulic systems drive right and left scraper, material feeding is convenient and prompt.

Traveling system

Imported pump,motor and speed reducer guarantee the reliability of transmission system;
 Travelling system adopts double pumps,double motors,double speed reducers ;
 Imported hydraulic plunger pump,italian imported planetary speed reducer;
 Exchangeable rubber track plate.

国机重工集团国际装备有限公司

SINOMACH-HI INTERNATIONAL EQUIPMENT CO., LTD.

Add:No.898 West Huang He Road, Changzhou city, Jiangsu Province, China

PC:213136

Tel:86-519-86781288 86752400

Fax:86-519-86781387

Http://www.sinomachiglobal.com

E-mail:sales@changlin.com.cn service@changlin.com.cn

