



Emagic Technology Co., LTD.

Address: RM206, No 1, No 146, Guanlan Avenue, Xinhe Community, Fucheng street,
Longhua district, Shenzhen, China TEL: 0755-27215455

Email: info@emagictek.com

W: www.emagictek.com

whatsapp: +86131 6479 0119

RF3132 SPECS--- Handheld RFID & barcode scanner

Physical Characteristics	
Colour	Black + orange
Battery	Rechargeable, 3000mAh Li-ion battery
Interfaces	Bluetooth BLE, SPP, HID, 2.4G
Keypad	barcode OR RFID scan, settings
Barcode	
Barcode Sensor	640*480 CMOS
Sensor field of view	Horizontal: 32°; Vertical: 24°
Decode capacity 1D	UPC-A, UPC-E, UPC-E1, EAN-8, EAN-13, EAN-14, EAN-128, UCC128, ISBN/ISSN, CODE11, CODE32, CODE39, CODE39 Full ASCII, CODE93, CODE128, China postal, UK/Plessey, GS1
Decode capacity 2D	QR code, PDF417, Data matrix, AZTEC, Maxicode, Micro PDF
RFID	
RFID (UHF)	Protocol standard: EPC G2/ISO 18000-6C;
	Working frequency: 860-960MHz
	Power: working voltage 3.6V-5V, RF output 5dBm to 27dbm (CE: 24dbm)
	Standby power consumption is about 0.25W, maximum 3.6W
	Reading distance: 0-80cm (depends on environment and tag)
	Multi-tags read rate > 100 tags per second
User Environment	
Operating Temp.	-10°C +50 °C
Storage Temp.	-20 °C~+70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.2m / 4ft. Drops to the concrete across the operating temperature range;

