

MXCF-1

Single phase thyristor trigger device

单相可控硅触发器



产品特点

Product Characteristics

- 触发器波形对称性好，控制精度<5%，线性化高，工作稳定。

触发功率大，可直接触发3000A以内的晶闸管。

多种控制信号，电位器(10K)，DC1-5V，DC2-10V，DC4-20mA。

设有软启动功能，上电软启动保护可控硅和负载不受冲击

设计新颖独特，无相序限制，接线简单，维护方便。

主电路与控制电路全隔离，安全可靠。

喷涂三防漆有一层透明保护膜，具有优越的防潮、防尘、防腐蚀性。

触发器设有事件或故障封锁触发脉冲功能。
- The trigger waveform symmetry is good, the control accuracy is <5%, the linearization is high, and the work is stable.

High trigger power, can directly trigger within 3000A thyristor.

Various control signals, potentiometer (10K), DC1-5V, DC2-10V, DC4-20mA.

With soft start function, soft start on the power to protect the thyristor and load from shock

Unique design, no phase sequence restrictions, simple wiring, easy maintenance.

The main circuit and the control circuit are completely isolated, safe and reliable.

Spraying three anti-paint has a layer of transparent protective film, with superior moisture, dust and corrosion resistance.

The trigger has the function of event or fault blocking trigger pulse.

外形及安装尺寸 / 接线图

Outline and mounting dimensions/wiring diagram (mm)

