

MXCF-3

Three phase thyristor trigger device

三相可控硅触发器



产品特点

Product Characteristics

- 触发器波形对称性好，控制精度<5%，线性化高，工作稳定。
 - 触发功率大，可直接触发3000A以内的晶闸管。
 - 多种控制信号，电位器(10K)，DC1-5V，DC2-10V，DC4-20mA。
 - 设有软启动功能，上电软启动保护可控硅和负载不受冲击
 - 设计新颖独特，无相序限制，接线简单，维护方便。
 - 主电路与控制电路全隔离，安全可靠。
 - 喷涂三防漆有一层透明保护膜，具有优越的防潮、防尘、防腐蝕性。
 - 触发器设有事件或故障封锁触发脉冲功能。
- The trigger waveform symmetry is good, the control accuracy is <5%, the linearization is high, and the work is stable.
 - High trigger power, can directly trigger within 3000A thyristor.
 - Various control signals, potentiometer (10K), DC1-5V, DC2-10V, DC4-20mA.
 - With soft start function, soft start on the power to protect the thyristor and load from shock
 - Unique design, no phase sequence restrictions, simple wiring, easy maintenance.
 - The main circuit and the control circuit are completely isolated, safe and reliable.
 - Spraying three anti-paint has a layer of transparent protective film, with superior moisture, dust and corrosion resistance.
 - The trigger has the function of event or fault blocking trigger pulse.



外形及安装尺寸 / 接线图

Outline and mounting dimensions/wiring diagram (mm)

